

Part number

CSAHM 16 N



Male insert, CSAH series, SQUICH® spring terminal connection without tools, 16 poles + PE (17-32), 16 A 250 V 4 kV 3, size "66.40"

Product description		Material properties	
Product type	Insert	Main material	Polycarbonate (PC)
Series	CSAH	Other materials	Contacts: copper alloy
Connection type	SQUICH® spring terminal connection without tools	Colour	RAL 7032 grey
Gender	Male	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	32 poles + 	China RoHs - EFUP	50
Size	Size "66.40"	REACH SVHC substances	Yes Lead
Technical data		SCIP number	1a9c93ff-0445-4a16-81e3-1609ac5274d6
Current	16 A	Approvals / Standards	
Voltage	250 V	Reference standard	EN 61984:2009-06
Rated impulse withstand voltage	4 kV	Certifications	DNV, BV, EAC, CQC
Pollution degree	3	UL	ECBT2
Rated voltage according to UL/CSA	600 V	cUL	ECBT8
Wire cross-section	0,14 mm² - 2,50 mm²	General ordering information	
AWG size	26 - 14	EAN13 code	8015747221443
Contact type	Turned silver plated	eCl@ss 8.1	27440205
Pole numbering system	17-32	ETIM 7.0	EC000438
IP degree of protection	IP20 without enclosure, IP65/IP66 with enclosure	Packaging Information	
Further technical details		Packaging length	260,00 mm
Characteristics according to EN 61984	16A 250V 4kV 3; 16A 230/400V 4kV 2	Packaging height	120,00 mm
Mating cycles	≥ 500	Packaging width	140,00 mm
Insulation resistance	≥ 10 GΩ	Packaging weight	2,20 kg
Contact resistance	≤ 3 mΩ	Packaging volume	4,37 dm³
Weight	64,00 g	Packaging description	Carton box
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging quantity	30 Pcs
Conductors stripping length	9...11 mm	Packaging EAN code	8015747222297
UL 94 flammability rating	V-0	Sub-packaging length	127,00 mm
Tightening torque for PE connection	M3,5: 0,8 Nm; 7,1 lb.in (Ph1 or 0,8 x 5,5 mm)	Sub-packaging height	45,00 mm
		Sub-packaging width	79,00 mm
		Sub-packaging weight	0,37 kg
		Sub-packaging volume	0,45 dm³
		Sub-packaging description	Carton tray
		Sub-packaging quantity	5 Pcs
		Sub-packaging EAN barcode	8015747221481