Part number C7P 24





Surface mounting housing, V-TYPE series, with 2 levers, Pg21 cable entry, size "104.27"

Product description

Product type Series Closing type Size

Surface mounting housing V-TYPE With 2 levers Size "104.27" With cable entry

Cable entry Technical data

IP degree of protection Further technical details Weight

Operating temperature range (min, max)

Pg21

IP66 / IP67 / IP69

368,00 g -40°C...+125°C

RoHs conformit
China RoHs - El
REACH SVHC su
Approvals / Sta
Certifications
UL
cUL
General orderin
EAN13 code
Packaging Info
Packaging leng
Packaging heig
Packaging widt


Material properties	
Other materials	Lever: Stainless steel Gasket: NBR
Colour	RAL 7040 grey
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No
Approvals / Standards	
Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8
General ordering information	
EAN13 code	8015747093569
Packaging Information	
Packaging length	300,00 mm
Packaging height	160,00 mm
Packaging width	180,00 mm
Packaging weight	3,93 kg
Packaging volume	8,64 dm³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747251143
Sub-packaging weight	1,97 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747178242

Part number C7P 24



Catalogue drawings

C7P - C7AP M7P - M7AP



Notes

C7P/M7P:

Due to the vertical closing movement, the new lever offers an IP66/IP67 protection (according to EN 60529) when fitted with a complete and coupled connector and used with ILME standard hoods in die cast aluminum with pegs (without adaptor).

Dimensions shown in mm are not binding and may be changed without notice.