

Part number

CHIN 24



Bulkhead mounting housing, LS-TYPE series,
with 2 levers, size "104.27"

Product description

Product type	Bulkhead mounting housing
Series	LS-TYPE
Closing type	With 2 levers
Size	Size "104.27"
Cable entry	Without cable entry

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	98,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163101
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Packaging length	250,00 mm
Packaging height	145,00 mm
Packaging width	300,00 mm
Packaging weight	1,96 kg
Packaging volume	10,88 dm ³
Packaging description	Carton box
Packaging quantity	20 Pcs
Packaging EAN code	8015747187626
Sub-packaging weight	0,49 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187633

Part number

CHIN 24



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures

size "104.27"

LS-TYPE version

inserts:

CD	64 poles + @	51+53 *
CT, CTS **)	64 poles + @	57 *
CDD	108 poles + @	64+66 *
CDE	46 poles + @	83+85 *
CSH	24 poles + @	91+93 *
CCE	24 poles + @	100+104 *
CNE, CSE, JCNE, JCSE	24 poles + @	101 and 109 *
CSS	24 poles + @	122+123 *
CTE, CTSE **)	24 poles + @	129 *
CMSE	10+2 (aux) poles + @	139 *
CMCE	10+2 (aux) poles + @	138 *
CX	4/8 poles + @	155 *
MIXO	6 modules	160+195 *

insert centre distance: 104 x 27 mm

* refer to catalogue page CN.12

housings with double lever

hoods with 4 pegs

description	part no.	entry	part no.	entry
		M		M
bulkhead mounting housing, with 2 levers	CHIN 24			
surface mounting housing, high construction, with 2 levers	MAPN 24.32	32		
with pegs, side entry			MHON 24.32	32
with pegs, side entry, high construction			MFON 24.32	32
with pegs, side entry			MHVN 24.32	32
with pegs, side entry, high construction			MFVN 24.32	32

** only in the CHIN 24 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

CHIN 24

MAPN 24.32

dimensions in mm

MFON 24.32

MFVN 24.32

MHON 24.32

MHVN 24.32

Notes

Dimensions shown in mm are not binding and may be changed without notice.