

Part number

# MLAV 16 LG40



Hood, IL-BRID series, with 1 lever, M40 top cable entry, size "77.27", high construction

| Product description                    |                                     | Material properties          |                                                              |
|----------------------------------------|-------------------------------------|------------------------------|--------------------------------------------------------------|
| Product type                           | Hood                                | Other materials              | Lever: Polyamide (PA) and Stainless steel core<br>Gasket NBR |
| Series                                 | IL-BRID                             | Colour                       | RAL 7040 grey                                                |
| Closing type                           | With 1 lever                        | RoHs conformity              | Compliant                                                    |
| Size                                   | Size 77.27                          | China RoHs - EFUP            | E                                                            |
| Cable entry                            | Top cable entry with adapter<br>M40 | REACH SVHC substances        | No                                                           |
| Specification                          | High construction                   | General ordering information |                                                              |
| Technical data                         |                                     | EAN13 code                   | 8015747288057                                                |
| IP degree of protection                | IP65 / IP66 / IP69                  | eCl@ss 8.1                   | 27440202                                                     |
| Further technical details              |                                     | ETIM 7.0                     | EC000437                                                     |
| Operating temperature range (min, max) | -40°C...+125°C                      | Packaging Information        |                                                              |
|                                        |                                     | Sub-packaging description    | Plastic packaging                                            |
|                                        |                                     | Sub-packaging quantity       | 5 Pcs                                                        |
|                                        |                                     | Sub-packaging EAN barcode    | 8015747294416                                                |

Part number

# MLAV 16 LG40



Catalogue drawings

