

Part number

CDCF 16



Female insert, CDC series, crimp connection,
16 poles + PE, 16 A 250 V 4 kV 3, size "66.16"

Product description		Material properties	
Product type	Insert	Main material	Polycarbonate (PC)
Series	CDC	Colour	RAL 7032 grey
Connection type	Crimp connection	RoHs conformity	Compliant
Gender	Female	China RoHs - EFUP	E
N. of poles	16 poles + 	REACH SVHC substances	No
Size	Size "66.16"	Approvals / Standards	
Technical data		Reference standard	EN 61984:2009-06
Current	16 A	Certifications	CSA, CQC, DNV, BV, EAC
Voltage	250 V	UL	ECBT2
Rated impulse withstand voltage	4 kV	cUL	ECBT8
Pollution degree	3	General ordering information	
Rated voltage according to UL/CSA	600 V	EAN13 code	8015747013444
IP degree of protection	IP20 without enclosure, IP65/IP66 with enclosure	eCl@ss 8.1	27440205
Further technical details		ETIM 7.0	EC000438
Characteristics according to EN 61984	16A 250V 4kV 3; 16A 230/400V 4kV 2	Packaging Information	
Mating cycles	≥ 500	Packaging length	260,00 mm
Insulation resistance	≥ 10 GΩ	Packaging height	120,00 mm
Contact resistance	≤ 1 mΩ	Packaging width	140,00 mm
Weight	34,60 g	Packaging weight	1,26 kg
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging volume	4,37 dm³
UL 94 flammability rating	V-0	Packaging description	Carton box
Tightening torque for PE connection	M3,5: 0,8 Nm; 7,1 lb.in (Ph1 or 0,8 x 5,5 mm)	Packaging quantity	30 Pcs
		Packaging EAN code	8015747013451
		Sub-packaging length	118,00 mm
		Sub-packaging height	32,00 mm
		Sub-packaging width	76,00 mm
		Sub-packaging weight	0,21 kg
		Sub-packaging volume	0,29 dm³
		Sub-packaging description	Carton tray
		Sub-packaging quantity	5 Pcs
		Sub-packaging EAN barcode	8015747013468

Part number

CDCF 16



Notes

California Proposition 65 Information



WARNING

This product can expose you to nickel compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
