

Part number
CQF 21



Female insert, CQ series, crimp connection, 21 poles, 6,5 A 50 V 0,8 kV 3, size "21.21"


Product description		Material properties	
Product type	Insert	Main material	Polycarbonate (PC)
Series	CQ	Colour	RAL 7032 grey
Connection type	Crimp connection	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Gender	Female	China RoHs - EFUP	50
N. of poles	21 poles	REACH SVHC substances	Yes Lead
Size	Size "21.21"	SCIP number	5a97d67d-dd49-45fe-94c0-411f951ef5ee
Specification	Standard & HNM (High Number of Matings)	Approvals / Standards	
Technical data		Certifications	DNV, BV
Current	5 A	UL	ECBT2
Voltage	50 V	cUL	ECBT8
Rated impulse withstand voltage	0,8 kV	General ordering information	
Pollution degree	3	EAN13 code	8015747235471
Rated voltage according to UL/CSA	50 V AC/120 V DC	eCl@ss 8.1	27440205
IP degree of protection	IP20 without enclosure, IP44/IP66/IP67/IP68/IP69 with enclosure	ETIM 7.0	EC000438
Further technical details		Packaging Information	
Characteristics according to EN 61984	6,5A 50V AC / 120V DC 0,8kV 3	Packaging length	210,00 mm
Mating cycles	≥ 500	Packaging height	200,00 mm
Insulation resistance	≥ 10 GΩ	Packaging width	130,00 mm
Contact resistance	≤ 4 mΩ	Packaging weight	1,90 kg
Weight	8,00 g	Packaging volume	5,46 dm ³
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging description	Carton box
UL 94 flammability rating	V-0	Packaging quantity	200 Pcs
Tightening torque for fixing screws	M3: 0,5 Nm; 4,4 lb.in (Ph1 or 0,8 x 5,5 mm)	Packaging EAN code	8015747235495
		Sub-packaging length	197,00 mm
		Sub-packaging height	35,00 mm
		Sub-packaging width	113,00 mm
		Sub-packaging weight	0,38 kg
		Sub-packaging volume	0,78 dm ³
		Sub-packaging description	Carton tray
		Sub-packaging quantity	40 Pcs
		Sub-packaging EAN barcode	8015747235501

Part number

CQF 21




Catalogue drawings



Derating curves

CQ 21 poles connector inserts
Maximum current load derating diagram



Notes