

Part number

MHVN 06 L25



Hood, LS-TYPE series, with 2 pegs, M25 top cable entry, size "44.27"

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 2 pegs
Size	Size 44.27
Cable entry	Top cable entry M25

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	84,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747194204
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Sub-packaging weight	0,42 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747123341

Part number

MHVN 06 L25



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures

size "44.27"

LS-TYPE version

inserts:

CDD	24 poles + @	59 *
CQE	10 poles + @	80 *
CSH	6 poles + @	88 *
CCE	6 poles + @	94 *
CNE, CSE, JONE, JCSE	6 poles + @ 96 and 106 *	118 *
CSS	6 poles + @	126 *
CTE, CTSE **)	6 poles + @	126 *
MIXO	2 modules	160+195 *

insert centre distance: 44 x 27 mm

* refer to catalogue page CN.12

housings with single lever

hoods with 2 pegs

description	part no.	entry M	part no.	entry M
bulkhead mounting housing, with lever	CHIN 06 L			
surface mounting housing, high construction, with lever	MAPN 06 L32	32		
with pegs, side entry			MHON 06 L25	25
with pegs, side entry, high construction			MFON 06 L25	25
with pegs, top entry			MHVN 06 L25	25
with pegs, top entry, high construction			MFVN 06 L25	25

** only in the CHIN 06 L enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions in mm

CHIN 06 L

MAPN 06 L32

dimensions in mm

MFON 06 L25

MFVN 06 L25

MHON 06 L25

MHVN 06 L25

IP65

dimensions shown are not binding and may be changed without notice

Notes