


Part number

CTF 10 L



Female insert, CT series, screw terminal connection, 10 poles + PE, 16 A 230/400 V 4 kV 2, size "57.27", with incorporated terminal block, left side mounting







Product description		Material properties	
Product type	Insert	Main material	Polycarbonate (PC)
Series	CT	Other materials	Contacts: copper alloy
Connection type	Screw terminal connection	Colour	RAL 7032 grey
Gender	Female	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	10 poles + 	China RoHs - EFUP	50
Size	Size 57.27	REACH SVHC substances	Yes Lead
Specification	Left side mounting With incorporated terminal block	SCIP number	1a9c93ff-0445-4a16-81e3-1609ac5274d6
Technical data		Approvals / Standards	
Current	16 A	Reference standard	EN 61984:2009-06
Voltage	230 - 400 V	Certifications	CSA, CQC, DNV, BV, EAC
Rated impulse withstand voltage	4 kV	UL	ECBT2
Pollution degree	2	General ordering information	
Rated voltage according to UL/CSA	600 V	EAN13 code	8015747040662
Wire cross-section	0,75 mm ² - 2,50 mm ²	eCl@ss 8.1	27440205
AWG size	18 - 14	ETIM 7.0	EC000438
Contact type	Turned silver plated	Packaging Information	
IP degree of protection	IP20 without enclosure, IP66/IP69 with enclosure	Packaging length	112,00 mm
Further technical details		Packaging height	95,00 mm
Characteristics according to EN 61984	10A 230/400V 4kV 3; 10A 400V 4kV 2	Packaging width	117,00 mm
Mating cycles	≥ 500	Packaging weight	0,56 kg
Insulation resistance	≥ 10 GΩ	Packaging volume	1,24 dm ³
Contact resistance	≤ 4 mΩ	Packaging description	Carton box
Weight	129,00 g	Packaging quantity	4 Pcs
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging EAN code	8015747040679
Conductors stripping length	12 mm	Sub-packaging weight	0,14 kg
UL 94 flammability rating	V-0	Sub-packaging description	Plastic packaging
Torque for main contact	M2,6: 0,4 Nm; 3,5 lb.in (0,5 x 3 mm)	Sub-packaging quantity	1 Pcs
Tightening torque for PE connection	M4: 1,2 Nm, 10,6 lb.in (Ph2 or 1,0x5,5mm)	Sub-packaging EAN barcode	8015747040686
Tightening torque for fixing screws	M3: 0.5 Nm; 4.4 lb.in (Ph1 or 0.8x4 mm)		

Part number


CTF 10 L



Catalogue drawings



Notes



California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
