


品番

CMEF 10 T



メス インサート, CME シリーズ, ネジ式結線, 10 + 2 極 + PE, 16 A 830 V 8 kV 3 / 16 A 500 V 6 kV 3, サイズ "104.27", プレート付き

製品説明

製品タイプ	インサート
シリーズ	CME
接続タイプ	ねじ式接続
性別	メス
極数	10極 +
補助極	2極
サイズ	サイズ"104.27"
仕様	電線保護板付

技術データ

電流	16 A
電圧	830 V
定格インパルス耐電圧	8 kV
汚染度	3
導体断面積	0,50 mm ² - 4,00 mm ²
AWG サイズ	20 - 12
コンタクトタイプ	切削コンタクト 銀メッキ
IP 保護等級	エンクロージャなしの場合IP20 エンクロージャ有りの場合IP65/IP66

技術詳細

重さ	93,50 g
動作温度範囲 (最小 最大)	-40 °C ... +125 °C

材料特性

主な素材	ポリカーボネート
その他の素材	銅合金
カラー	RAL 7032
SCIP番号	1a9c93ff-0445-4a16-81e3-1609ac5274d6
認証 / 規格	
参照	EN 61984:2009-06
認証	CSA, CQC, DNV, BV, EAC
UL	ECBT2
cUL	ECBT8

ジェネラルオーダーリングインフォメーション

EAN13 コード	8015747127912
-----------	---------------

パッケージ情報

パッケージ長さ	270,00 mm
パッケージ高さ	75,00 mm
パッケージ幅	180,00 mm
パッケージ重量	3,12 kg
パッケージ体積	3,65 dm ³
パッケージ 詳細	カートンボックス
パッケージ 数量	30 個
パッケージ EAN コード	8015747128070
サブパッケージ 長さ	113,00 mm
サブパッケージ 高さ	36,00 mm
サブパッケージ 幅	180,00 mm
サブパッケージ 重量	0,52 kg
サブパッケージ 体積	0,73 dm ³
サブパッケージ 詳細	カートントレイ
サブパッケージ 数量	5 個
サブパッケージ EAN パーコード	8015747128087

品番


CMEF 10 T





カタログ図面

カタログ図面

CMEM 10



CMEF 10



メモ

mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.