


品番

CNEM 24 T



オス インサート, CNE シリーズ, ネジ式結線, 24
極 + PE, 16 A 500 V 6 kV 3, サイズ "104.27",
プレート付き

製品説明	
製品タイプ	インサート
シリーズ	CNE
接続タイプ	ねじ式接続
性別	オス
極数	24極 +
サイズ	サイズ"104.27"
仕様	電線保護板付
技術データ	
電流	16 A
電圧	500 V
定格インパルス耐電圧	6 kV
汚染度	3
導体断面積	0,50 mm ² - 4,00 mm ²
AWG サイズ	20 - 12
コンタクトタイプ	切削コンタクト 銀メッキ
IP 保護等級	エンクロージャなしの場合IP20 エンクロージャ 有りの場合IP65/IP66/IP68/IP69
技術詳細	
重さ	111,00 g
動作温度範囲 (最小 最大)	-40 °C ... +125 °C



材料特性	
主な素材	ポリカーボネート
その他の素材	銅合金
カラー	RAL 7032
SCIP番号	1a9c93ff-0445-4a16-81e3-1609ac5274d6
認証 / 規格	
参照	EN 61984:2009-06
認証	CSA, CQC, DNV, BV, EAC
UL	ECBT2, PVVA2
cUL	ECBT8, PVVA8
ジェネラルオーダリングインフォメーション	
EAN13 コード	8015747033305
ecl@ss 分類	27440205
ETIM 分類	EC000438
パッケージ情報	
パッケージ長さ	270,00 mm
パッケージ高さ	75,00 mm
パッケージ幅	180,00 mm
パッケージ重量	3,65 kg
パッケージ体積	3,65 dm ³
パッケージ 詳細	カートンボックス
パッケージ 数量	30 個
パッケージ EAN コード	8015747033312
サブパッケージ 長さ	113,00 mm
サブパッケージ 高さ	36,00 mm
サブパッケージ 幅	180,00 mm
サブパッケージ 重量	0,61 kg
サブパッケージ 体積	0,73 dm ³
サブパッケージ 詳細	カートントレイ
サブパッケージ 数量	5 個
サブパッケージ EAN パーコード	8015747033329

品番


CNEM 24 T



カタログ図面



カタログ図面



メモ

mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
