

品番

CPM 06 N



オス インサート, CP シリーズ, ネジ式結線, 6 極 + PE, 35 A 400/690 V 6 kV 3, サイズ "77.62", 黒, プレート付き

製品説明	
製品タイプ	インサート
シリーズ	CP
接続タイプ	ねじ式接続
性別	オス
極数	12極 +
サイズ	サイズ"77.62"
仕様	黒色 電線保護板付
技術データ	
電流	35 A
電圧	400 - 690 V
定格インパルス耐電圧	6 kV
汚染度	3
導体断面積	0,75 mm ² - 6,00 mm ²
AWG サイズ	18 - 10
コンタクトタイプ	切削コンタクト 銀メッキ
IP 保護等級	エンクロージャなしの場合IP20 エンクロージャ有りの場合IP65/IP66
技術詳細	
重さ	77,00 g
動作温度範囲 (最小 最大)	-40 °C ... +125 °C

材料特性	
主な素材	ポリカーボネート
その他の素材	銅合金
カラー	RAL 9005
SCIP番号	1a9c93ff-0445-4a16-81e3-1609ac5274d6
認証 / 規格	
参照	EN 61984:2009-06
認証	CSA, CQC, DNV, BV, EAC
UL	ECBT2
ジェネラルオーダリングインフォメーション	
EAN13 コード	8015747036924
ecl@ss 分類	27440205
ETIM 分類	EC000438
パッケージ情報	
パッケージ長さ	210,00 mm
パッケージ高さ	200,00 mm
パッケージ幅	130,00 mm
パッケージ重量	1,75 kg
パッケージ体積	5,46 dm ³
パッケージ 詳細	カートンボックス
パッケージ 数量	20 個
パッケージ EAN コード	8015747261623
サブパッケージ 長さ	87,00 mm
サブパッケージ 高さ	36,00 mm
サブパッケージ 幅	180,00 mm
サブパッケージ 重量	0,44 kg
サブパッケージ 体積	0,56 dm ³
サブパッケージ 詳細	カートントレイ
サブパッケージ 数量	5 個
サブパッケージ EAN バーコード	8015747036931


品番

CPM 06 N




カタログ図面


CPM 06



CPF 06



カタログ図面



メモ

mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
