

Part number

CX 02 4HF



Female modular insert, Mixo series, crimp connection, 2 poles, 2 modules, 40 A 2900/5000 V 15 kV 3, with heat-shrinking tube

Product description		Material properties	
Product type	Modular insert	Main material	Polycarbonate
Series	Mixo	Colour	RAL 7032 grey
Connection type	Crimp connection	RoHs conformity	Compliant
Gender	Female	China RoHs - EFUP	E
N. of poles	2 poles	REACH SVHC substances	No
Size	2 modules	Approvals / Standards	
Specification	With heat-shrinking tube	Certifications	DNV
Technical data		General ordering information	
Current	40 A	EAN13 code	8015747271394
Voltage	2900 - 5000 V	eCl@ss 8.1	27440205
Rated impulse withstand voltage	15 kV	ETIM 7.0	EC000438
Pollution degree	3	Packaging Information	
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	Sub-packaging weight	0,05 kg
Further technical details		Sub-packaging description	Plastic bag
Characteristics according to EN 61984	40 A 2900/5000 V 15 kV 3	Sub-packaging quantity	1 Pcs
Mating cycles	≥ 500	Sub-packaging EAN barcode	8015747271400
Insulation resistance	≥ 10 GΩ		
Contact resistance	≤ 0,3 mΩ		
Weight	53,00 g		
Operating temperature range (min, max)	-40 °C ... +125 °C		
UL 94 flammability rating	V-0		

Part number

CX 02 4HF



Derating curves

