

Part number

# MHON 06 L25



Hood, LS-TYPE series, with 2 pegs, M25 side cable entry, size "44.27"

#### Product description

|                     |                         |
|---------------------|-------------------------|
| <b>Product type</b> | Hood                    |
| <b>Series</b>       | LS-TYPE                 |
| <b>Closing type</b> | With 2 pegs             |
| <b>Size</b>         | Size 44.27              |
| <b>Cable entry</b>  | Side cable entry<br>M25 |

#### Technical data

|                                |      |
|--------------------------------|------|
| <b>IP degree of protection</b> | IP65 |
|--------------------------------|------|

#### Further technical details

|                                               |                |
|-----------------------------------------------|----------------|
| <b>Weight</b>                                 | 95,00 g        |
| <b>Operating temperature range (min, max)</b> | -40°C...+125°C |

#### Material properties

|                              |                |
|------------------------------|----------------|
| <b>Colour</b>                | RAL 9005 black |
| <b>RoHs conformity</b>       | Compliant      |
| <b>China RoHs - EFUP</b>     | E              |
| <b>REACH SVHC substances</b> | No             |

#### Approvals / Standards

|                       |         |
|-----------------------|---------|
| <b>Certifications</b> | DNV, BV |
| <b>UL</b>             | ECBT2   |
| <b>cUL</b>            | ECBT8   |

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747194181 |
| <b>eCl@ss 8.1</b> | 27440202      |
| <b>ETIM 7.0</b>   | EC000437      |

#### Packaging Information


|                                  |                   |
|----------------------------------|-------------------|
| <b>Sub-packaging weight</b>      | 0,48 kg           |
| <b>Sub-packaging description</b> | Plastic packaging |
| <b>Sub-packaging quantity</b>    | 5 Pcs             |
| <b>Sub-packaging EAN barcode</b> | 8015747194198     |

Part number

MHON 06 L25



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures

size "44.27"

LS-TYPE version

inserts:

|                      |                          |           |
|----------------------|--------------------------|-----------|
| CDD                  | 24 poles + 0             | 59 *      |
| CQE                  | 10 poles + 0             | 80 *      |
| CSH                  | 6 poles + 0              | 88 *      |
| CCE                  | 6 poles + 0              | 94 *      |
| CNE, CSE, JONE, JCSE | 6 poles + 0 95 and 106 * | 118 *     |
| CSS                  | 6 poles + 0              | 126 *     |
| CTE, CTSE **)        | 6 poles + 0              | 126 *     |
| MIXO                 | 2 modules                | 160+195 * |

insert centre distance: 44 x 27 mm

\* refer to catalogue page CN.12

housings with single lever

hoods with 2 pegs

| description                                             | part no.    | entry | part no.    | entry |
|---------------------------------------------------------|-------------|-------|-------------|-------|
| bulkhead mounting housing, with lever                   | CHIN 06 L   | M     |             |       |
| surface mounting housing, high construction, with lever | MAPN 06 L32 | 32    |             |       |
| with pegs, side entry                                   |             |       | MHON 06 L25 | 25    |
| with pegs, side entry, high construction                |             |       | MFON 06 L25 | 25    |
| with pegs, top entry                                    |             |       | MHVN 06 L25 | 25    |
| with pegs, top entry, high construction                 |             |       | MFVN 06 L25 | 25    |

\*\* only in the CHIN 06 L enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions in mm

CHIN 06 L

MAPN 06 L32

dimensions in mm

MFON 06 L25

MFVN 06 L25

MHON 06 L25

MHVN 06 L25

4