

Part number

# MHON 24.32



Hood, LS-TYPE series, with 4 pegs, M32 side cable entry, size "104.27"

#### Product description

|                     |                         |
|---------------------|-------------------------|
| <b>Product type</b> | Hood                    |
| <b>Series</b>       | LS-TYPE                 |
| <b>Closing type</b> | With 4 pegs             |
| <b>Size</b>         | Size "104.27"           |
| <b>Cable entry</b>  | Side cable entry<br>M32 |

#### Technical data

|                                |      |
|--------------------------------|------|
| <b>IP degree of protection</b> | IP65 |
|--------------------------------|------|

#### Further technical details

|                                               |                |
|-----------------------------------------------|----------------|
| <b>Weight</b>                                 | 197,00 g       |
| <b>Operating temperature range (min, max)</b> | -40°C...+125°C |

#### Material properties

|                              |                |
|------------------------------|----------------|
| <b>Colour</b>                | RAL 9005 black |
| <b>RoHs conformity</b>       | Compliant      |
| <b>China RoHs - EFUP</b>     | E              |
| <b>REACH SVHC substances</b> | No             |

#### Approvals / Standards

|                       |         |
|-----------------------|---------|
| <b>Certifications</b> | DNV, BV |
| <b>UL</b>             | ECBT2   |
| <b>cUL</b>            | ECBT8   |

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747194303 |
| <b>eCl@ss 8.1</b> | 27440202      |
| <b>ETIM 7.0</b>   | EC000437      |

#### Packaging Information


|                                  |                   |
|----------------------------------|-------------------|
| <b>Sub-packaging weight</b>      | 0,99 kg           |
| <b>Sub-packaging description</b> | Plastic packaging |
| <b>Sub-packaging quantity</b>    | 5 Pcs             |
| <b>Sub-packaging EAN barcode</b> | 8015747194310     |

Part number

# MHON 24.32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures

size "104.27"

LS-TYPE version

inserts:

|                      |                      |               |
|----------------------|----------------------|---------------|
| CD                   | 64 poles + @         | 51+53 *       |
| CT, CTS **)          | 64 poles + @         | 57 *          |
| CDD                  | 108 poles + @        | 64+66 *       |
| CDE                  | 46 poles + @         | 83+85 *       |
| CSH                  | 24 poles + @         | 91+93 *       |
| CCE                  | 24 poles + @         | 100+104 *     |
| CNE, CSE, JCNE, JCSE | 24 poles + @         | 101 and 109 * |
| CSS                  | 24 poles + @         | 122+123 *     |
| CTE, CTSE **)        | 24 poles + @         | 129 *         |
| CMSE                 | 10+2 (aux) poles + @ | 139 *         |
| CMCE                 | 10+2 (aux) poles + @ | 138 *         |
| CX                   | 4/8 poles + @        | 155 *         |
| MIXO                 | 6 modules            | 160+195 *     |

insert centre distance: 104 x 27 mm

\* refer to catalogue page CN.12

housings with double lever

hoods with 4 pegs

| description                                                | part no.   | entry | part no.   | entry |
|------------------------------------------------------------|------------|-------|------------|-------|
| bulkhead mounting housing, with 2 levers                   | CHIN 24    | M     |            |       |
| surface mounting housing, high construction, with 2 levers | MAPN 24.32 | 32    |            |       |
| with pegs, side entry                                      |            |       | MHON 24.32 | 32    |
| with pegs, side entry, high construction                   |            |       | MFON 24.32 | 32    |
| with pegs, side entry                                      |            |       | MHVN 24.32 | 32    |
| with pegs, side entry, high construction                   |            |       | MFVN 24.32 | 32    |

\*\* only in the CHIN 24 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

CHIN 24

MAPN 24.32

dimensions in mm

MFON 24.32

MFVN 24.32

MHON 24.32

MHVN 24.32