

Part number

CX 08 CF



Female modular insert, Mixo series, crimp connection, 8 poles, 1 module, 16 A 400 V 6 kV 3

Product description		Material properties	
Product type	Modular insert	Main material	Polycarbonate
Series	Mixo	Colour	RAL 7032 grey
Connection type	Crimp connection	RoHs conformity	Compliant
Gender	Female	China RoHs - EFUP	E
N. of poles	8 poles	REACH SVHC substances	No
Size	1 module	Approvals / Standards	
Specification	Standard & HNM (High Number of Matings)	Reference standard	EN 61984:2009-06
Technical data		Certifications	CSA, CQC, DNV, BV, EAC
Current	16 A	General ordering information	
Voltage	400 V	EAN13 code	8015747129237
Rated impulse withstand voltage	6 kV	eCl@ss 8.1	27440205
Pollution degree	3	ETIM 7.0	EC000438
Rated voltage according to UL/CSA	600 V	Packaging Information	
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	Packaging length	180,00 mm
Further technical details		Packaging height	120,00 mm
Characteristics according to EN 61984	16A 400V 6kV 3; 16A 400/690V 6kV 2	Packaging width	155,00 mm
Insulation resistance	≥ 10 GΩ	Packaging weight	0,71 kg
Contact resistance	≤ 1 mΩ	Packaging volume	3,35 dm ³
Weight	8,70 g	Packaging description	Carton box
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging quantity	60 Pcs
UL 94 flammability rating	V-0	Packaging EAN code	8015747221290
		Sub-packaging length	35,00 mm
		Sub-packaging height	40,00 mm
		Sub-packaging width	155,00 mm
		Sub-packaging weight	0,12 kg
		Sub-packaging volume	0,22 dm ³
		Sub-packaging description	Carton tray
		Sub-packaging quantity	10 Pcs
		Sub-packaging EAN barcode	8015747129244





Part number

CX 08 CF





Catalogue drawings

CX 08 CM



CX 08 CF



Catalogue drawings

