Part number

C30MA 95





Male crimp contact, C30 series, 300 A, turned silver plated, wire cross section 95 mm², AWG 3/0


Product description			
Product type	Crimp contact		
Series	C30		
Gender	Male		
Technical data			
Current	300 A		
Wire cross-section	95,00 mm²		
Contact type	Turned silver plated		
Further technical details			
Contact resistance	≤ 0,2 mΩ		
Weight	49,60 g		
Conductors stripping length	22,5 mm		

Material properties					
Main material	Copper alloy				
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight				
China RoHs - EFUP	50				
REACH SVHC substances	Yes Lead				
General ordering information					
EAN13 code	8015747290470				
Packaging Information					
Packaging length	112,00 mm				
Packaging height	95,00 mm				
Packaging width	117,00 mm				
Packaging volume	1,24 dm³				
Packaging description	Carton box				
Packaging quantity	40 Pcs				
Packaging EAN code	8015747290500				
Sub-packaging description	Plastic box				
Sub-packaging quantity	5 Pcs				
Sub-packaging EAN barcode	8015747290517				

C30MA 95



Catalogue drawings



C30MA contacts

OSOFIA CONTUCTS						
conductor	conductor		2. 15	conductor		
section	slot ø A	øΒ	С	stripping		
(mm²)	(mm)	(mm)	(mm)	length (mm)		
16	5,5	18	42,7	19		
25	7	18	42,7	19		
35	8,2	18	43,7	20		
50	10	18	49,2	22,5		
70	11,5	18	49,2	22,5		
95	13,5	21	49,2	22,5		
120	15,5	21	49,2	22,5		

Notes

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

Dimensions shown in mm are not binding and may be changed without notice.