

Part number

CHIN 06 L



Bulkhead mounting housing, LS-TYPE series,
with 1 lever, size "44.27"

Product description

Product type	Bulkhead mounting housing
Series	LS-TYPE
Closing type	With 1 lever
Size	Size 44.27
Cable entry	Without cable entry

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	65,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747161596
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information








Packaging length	255,00 mm
Packaging height	195,00 mm
Packaging width	245,00 mm
Packaging weight	2,60 kg
Packaging volume	12,18 dm ³
Packaging description	Carton box
Packaging quantity	40 Pcs
Packaging EAN code	8015747187565
Sub-packaging weight	0,33 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187572

CHIN 06 L



Technical drawing of a rectangular plate with the following dimensions and specifications:

- Overall width: 32
- Overall height: 83
- Inner rectangular area width: 28
- Inner rectangular area height: 65
- Four circular holes, each with a diameter of $\varnothing 4.5$.
- The holes are positioned at the corners of the inner rectangular area.

CH.N - MA, MF.N enclosures		size "44.27"	LS-TYPE version	
<p>inserts: page</p> <p>CDD 24 poles + @ 59 *</p> <p>CQE 10 poles + @ 80 *</p> <p>CSH 6 poles + @ 88 *</p> <p>CCE 6 poles + @ 94 *</p> <p>CNE, CSE, J.CNE, J.CSE 6 poles + @ 95 and 105 *</p> <p>CSS 6 poles + @ 118 *</p> <p>CTE, CTSE ** 6 poles + @ 126 *</p> <p>MIXO 2 modules 160+195 *</p> <p>insert centre distance: 44 x 27 mm</p> <p>* refer to catalogue page CN.12</p>		<p>housings with single lever</p> 	<p>hoods with 2 pegs</p> 	
description	part no.	entry	part no.	entry
bulkhead mounting housing, with lever	CHIN 06 L			
surface mounting housing, high construction, with lever	MAPN 06 L32	32		
with pegs, side entry			MHON 06 L25	25
with pegs, side entry, high construction			MFON 06 L25	25
with pegs, top entry			MHVN 06 L25	25
with pegs, top entry, high construction			MFVN 06 L25	25
**) only in the CHIN 06 L enclosure				
panel cut-out for bulkhead mounting housing in mm	dimensions in mm		dimensions in mm	
	<p>CHIN 06 L</p> 		<p>MFON 06 L25</p> 	
<p>- kiln powder coating with RAL 9005 black epoxy polyester powder</p> <p>- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>	<p>MAPN 06 L32</p> 		<p>MFVN 06 L25</p> 	
			MHON 06 L25	
			MHVN 06 L25	

Notes

Dimensions shown in mm are not binding and may be changed without notice.