Part number CNZ 16 PV





Complete connector, CNZ series, composed of 2 screw terminal connection inserts with 16 poles + PE, and surface mounting housing with 2 levers and hood with top cable entry

Product description		Material properties	
Product type	Complete connector	Colour	RAL 7040 grey
Series	CNZ		Compliant with exemption
Connection type	Screw terminal connection	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Size	Size 77.27	China RoHs - EFUP	50
N. of poles	16 poles +		Yes
Cable entry	Pg21	REACH SVHC substances	Lead
Specification	Surface mounting housing with 2 levers and hood with top cable entry	SCIP number	A54fce24-f9c5-479f-a7e4-adb75fec7abe
		Approvals / Standards	
Technical data		Reference standard	EN 61984:2009-06
Current	16 A	Certifications	EAC
Voltage	500 V	General ordering information	
Rated impulse withstand voltage	6 kV	EAN13 code	8015747118965
		Packaging Information	
Pollution degree	3	Packaging length	310,00 mm
Wire cross-section	0,50 mm² - 2,50 mm²	Packaging height	260,00 mm
AWG size	20 - 14	Packaging width	325,00 mm
Contact type	Turned silver plated	Packaging weight	8,60 kg
IP degree of protection	IP65 / IP66 / IP69	Packaging volume	26,20 dm ³
Further technical details		Packaging description	Carton box
Weight	410,00 g	Packaging quantity	20 Pcs
		Packaging EAN code	8015747119016
		Sub-packaging weight	0,43 kg
		Sub-packaging description	Plastic bag

Sub-packaging quantity

Sub-packaging EAN

barcode

1 Pcs

8015747224215

Part number CNZ 16 PV



Notes

Dimensions shown in mm are not binding and may be changed without notice.

