

Part number

CR 26 V



Short screws, kit with 2 pcs




| Product description | | Material properties | |
|----------------------------------------|------------------|------------------------------|--------------------------------------------------------------------------------|
| Product type | Short screws | RoHS conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| Specification | Kit with 2 pcs | China RoHS - EFUP | 50 |
| Further technical details | | REACH SVHC substances | Yes Lead |
| Weight | 19,00 g | SCIP number | 308135ef-1d8f-45dc-a290-1478c89611e1 |
| Operating temperature range (min, max) | -40°C ... +125°C | General ordering information | |
| | | EAN13 code | 8015747114608 |
| | | eCl@ss 8.1 | 27449290 |
| | | ETIM 7.0 | EC002943 |
| Packaging Information | | | |
| | | Sub-packaging weight | 0,02 kg |
| | | Sub-packaging description | Plastic bag |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747114639 |

Part number

CR 26 V



Catalogue drawings



Notes

Dimensions shown in mm are not binding and may be changed without notice.

1. panel
2. mobile part
3. fixed part

In the fixed part, a pair of CR SP supports is fitted on the connector, using its securing screws. A CR..FS or CR..SS anchorage is fitted on the supports, using the supplied securing screws and washers. All parts are secured on the rear panel with the pair of CR 26 V viton screws.

In the mobile part too, a pair of CR SP supports are fitted on the connector and a CR..FS or CR..SS anchorage is secured on it. The pair of CR 42 V screws

fasten the mobile part to the fixed part.

Note: By unscrewing the CR 26 V panel screws, the whole assembly (mobile part + fixed part) can be removed from the panel for inspection.

