

Part number

# CW 3 SC50



Male fibre optic connector, CW SC patch cords series, GL fibre G50/125, orange, 3 m cable, for multi-module fibres

#### Product description

##### Technical data

**IP degree of protection** IP20

##### Further technical details

**Operating temperature range (min, max)** -5 °C ... +55 °C

#### Material properties

**RoHs conformity** Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight

**China RoHs - EFUP** 50

**REACH SVHC substances** Yes  
Lead

**SCIP number** 8b60cf05-8f5f-42af-80f1-e79cea373159

#### General ordering information

**EAN13 code** 8015747032544

**eCl@ss 8.1** 27061003

**ETIM 7.0** EC001263

#### Packaging Information

**Sub-packaging description** Plastic bag

**Sub-packaging quantity** 1 Pcs

**Sub-packaging EAN barcode** 8015747033459

Part number

**CW 3 SC50**



---

## Notes

Fiber type: multi-mode, graded index (GI), polished-terminated (PC)

Fiber designation: OM2

Insertion loss:  $\leq 0,25$  dB

Return loss:  $\geq 40$  dB

Fiber height:  $-50 \div +100$  nm

---

Cable diameter:  $2 \times \varnothing 2,8$  mm

Relative humidity: 95 %

Apex offset:  $\leq 50$   $\mu$ m

Radius: 5 to 25 mm

---