

Part number

CX 01 BCM



Male modular insert, Mixo Bus series, coaxial,
1 pole, 16 A 50 V 0,8 kV 3, shielded

Product description		Material properties	
Product type	Modular insert	Main material	Polycarbonate
Series	Mixo Bus	Colour	RAL 7032 grey
Connection type	Coaxial	RoHs conformity	Compliant
Gender	Male	China RoHs - EFUP	E
N. of poles	1 pole	REACH SVHC substances	No
Specification	Shielded	Approvals / Standards	
Technical data		Reference standard	EN 61984:2009-06
Current	16 A	Certifications	CSA, CQC, DNV, EAC
Voltage	50 V	UL	ECBT2
Rated impulse withstand voltage	0,8 kV	cUL	ECBT8
Pollution degree	3	General ordering information	
Rated voltage according to UL/CSA	50 V	EAN13 code	8015747178341
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	eCl@ss 8.1	27440205
Further technical details		ETIM 7.0	EC000438
Characteristics according to EN 61984	16A 50V 0.8kV 3	Packaging Information	
Insulation resistance	≥ 10 GΩ	Packaging length	112,00 mm
Contact resistance	≤ 1 mΩ	Packaging height	95,00 mm
Weight	28,00 g	Packaging width	117,00 mm
Operating temperature range (min, max)	-40°C ... +85°C	Packaging weight	0,30 kg
UL 94 flammability rating	V-0	Packaging volume	1,24 dm ³
		Packaging description	Carton box
		Packaging quantity	10 Pcs
		Packaging EAN code	8015747178358
		Sub-packaging weight	0,03 kg
		Sub-packaging description	Plastic bag
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747178365

Part number

CX 01 BCM



Notes

Standard modular inserts:

-in combination with standard contacts and standard frames (CX ... TF/TM); must be mounted either in traditional enclosures or in COB panel supports (both up to 500 matings).

Dimensions shown in mm are not binding and may be changed without notice.
