

Part number

DPTCM 15



Male insert,D-SUB, crimp connection, 15 poles

| Product description | | Material properties | |
|--|--|------------------------------|--------------------|
| Product type | Data connector | Main material | Polycarbonate (PC) |
| Series | D-SUB | RoHs conformity | Compliant |
| Connection type | Crimp connection | China RoHs - EFUP | E |
| Gender | Male | REACH SVHC substances | No |
| N. of poles | 15 poles | General ordering information | |
| Size | DA-15 | EAN13 code | 8015747287296 |
| Technical data | | Packaging Information | |
| Current | 5 A | Sub-packaging description | Plastic bag |
| Voltage | 50 V | Sub-packaging quantity | 1 Pcs |
| Rated impulse withstand voltage | 1 | Sub-packaging EAN barcode | 8015747184687 |
| Pollution degree | 3 | | |
| Further technical details | | | |
| Characteristics according to EN 61984 | With turned contacts: 7 A / with stamped contacts: 5 A | | |
| Insulation resistance | ≥ 10 GΩ | | |
| Weight | 6,00 g | | |
| Operating temperature range (min, max) | -55 °C ... +125 °C | | |
| UL 94 flammability rating | V-0 | | |

Part number

DPTCM 15



Notes

Dimensions shown in mm are not binding and may be changed without notice.
