



Part number JKF 03



Brief description:

female insert, 3 poles + PE, screw terminal connections, 10A, 230V/400V, 4kV, 3, tin plated, size "21.21", JEI insert series

Product description		Approvals / Standards	
Model	female insert	Reference standard	EN 61984:2009-06
Version	screw terminal connections	Quality mark	 , DNV GL, BV, EAC
Series	JK	Conformity	CQC, CE
Product type	with female contacts	General ordering information	
Family	JEI® inserts	EAN13 code	8015747209434
Size	size "21.21"	Tariff number	
N. of poles	3 poles + 	Packaging Information	
Technical data		Packaging length	210,00 mm
Current	10 A	Packaging height	200,00 mm
Voltage	230 - 400 V	Packaging width	130,00 mm
Rated impulse withstand voltage	4 kV	Packaging weight	2,95 kg
Pollution degree	3	Packaging volume	5,46 dm ³
Wire cross-section	0,75 mm ² - 2,50 mm ²	Packaging description	Carton box
AWG size	18 - 14	Packaging quantity	200 Pcs
Operating temperature range (min, max)	-40°C ... +100°C	Packaging EAN code	8015747209595
Contact material	tin plated	Sub-packaging weight	0,59 kg
Mating cycles	≥ 200	Sub-packaging description	Carton tray
IP degree of protection	IP20 without enclosure, IP44/IP66/IP67/IP68/IP69 with enclosure	Sub-packaging quantity	40 Pcs
		Sub-packaging EAN barcode	8015747209601
Further technical details			
Characteristics according to EN 61984	10A 230/400V 4kV 3; 10A 400/690V 4kV 2		
Insulation resistance	≥ 10 GΩ		
Rated voltage according to UL/CSA	600V		
UL 94 flammability rating	V-1		
Weight	15,75 g		