

Part number

MAPN 10.32



Surface mounting housing, LS-TYPE series, with 2 levers, M32 cable entry, size "57.27", high construction

Product description

Product type	Surface mounting housing
Series	LS-TYPE
Closing type	With 2 levers
Size	Size 57.27
Cable entry	With cable entry M32
Specification	High construction

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	380,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163125
eCl@ss 8.1	27440202
ETIM 7.0	EC000437


Packaging Information

Packaging length	475,00 mm
Packaging height	200,00 mm
Packaging width	150,00 mm
Packaging weight	5,10 kg
Packaging volume	14,25 dm ³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747249164
Sub-packaging weight	2,55 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187657

Part number MAPN 10.32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "57.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CDD	42 poles + ⊕ 61 *		
CQE	18 poles + ⊕ 81 *		
CSH	10 poles + ⊕ 89 *		
CCE	10 poles + ⊕ 90 *		
CNE, CSE, JONE, JCSE	10 poles + ⊕ 97 and 107 *		
CSS	10 poles + ⊕ 119 *		
CTE, CTSE **)	10 poles + ⊕ 127 *		
CMSE	3+2 (aux) poles + ⊕ 135 *		
CMCE	3+2 (aux) poles + ⊕ 134 *		
CX	8/24 poles + ⊕ 151 *		
MIXO	3 modules 160+195 *		

insert centre distance: 57 x 27 mm

* refer to catalogue page CN.12

description	part no.		part no.	
	entry	M	entry	M
bulkhead mounting housing, with 2 levers	CHIN 10			
surface mounting housing, high construction, with 2 levers	MAPN 10.32 32			
with pegs, side entry			MHON 10.25 25	25
with pegs, side entry, high construction			MFON 10.32 32	32
with pegs, top entry			MHVN 10.25 25	25
with pegs, top entry, high construction			MFVN 10.32 32	32

**) only in the CHIN 10 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

6

Notes

Dimensions shown in mm are not binding and may be changed without notice.