

Part number

# MAPN 10.32



Surface mounting housing, LS-TYPE series, with 2 levers, M32 cable entry, size "57.27", high construction

#### Product description

|                      |                          |
|----------------------|--------------------------|
| <b>Product type</b>  | Surface mounting housing |
| <b>Series</b>        | LS-TYPE                  |
| <b>Closing type</b>  | With 2 levers            |
| <b>Size</b>          | Size 57.27               |
| <b>Cable entry</b>   | With cable entry<br>M32  |
| <b>Specification</b> | High construction        |

#### Technical data

|                                |      |
|--------------------------------|------|
| <b>IP degree of protection</b> | IP65 |
|--------------------------------|------|

#### Further technical details

|   |                |
|---|----------------|
| <b>Weight</b>                                 | 380,00 g       |
| <b>Operating temperature range (min, max)</b> | -40°C...+125°C |

#### Material properties

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Other materials</b>       | Lever: Polyamide (PA)<br>Gasket: NBR |
| <b>Colour</b>                | RAL 9005 black                       |
| <b>RoHs conformity</b>       | Compliant                            |
| <b>China RoHs - EFUP</b>     | E                                    |
| <b>REACH SVHC substances</b> | No                                   |

#### Approvals / Standards

|                       |         |
|-----------------------|---------|
| <b>Certifications</b> | DNV, BV |
| <b>UL</b>             | ECBT2   |
| <b>cUL</b>            | ECBT8   |

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747163125 |
| <b>eCl@ss 8.1</b> | 27440202      |
| <b>ETIM 7.0</b>   | EC000437      |

#### Packaging Information

|                                  |                       |
|----------------------------------|-----------------------|
| <b>Packaging length</b>          | 475,00 mm             |
| <b>Packaging height</b>          | 200,00 mm             |
| <b>Packaging width</b>           | 150,00 mm             |
| <b>Packaging weight</b>          | 5,10 kg               |
| <b>Packaging volume</b>          | 14,25 dm <sup>3</sup> |
| <b>Packaging description</b>     | Carton box            |
| <b>Packaging quantity</b>        | 10 Pcs                |
| <b>Packaging EAN code</b>        | 8015747249164         |
| <b>Sub-packaging weight</b>      | 2,55 kg               |
| <b>Sub-packaging description</b> | Plastic packaging     |
| <b>Sub-packaging quantity</b>    | 5 Pcs                 |
| <b>Sub-packaging EAN barcode</b> | 8015747187657         |

# Part number MAPN 10.32



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures** size "57.27" **LS-TYPE version**

| inserts:                   | page                      | housings with double lever | hoods with 4 pegs |
|----------------------------|---------------------------|----------------------------|-------------------|
| CDD .....                  | 42 poles + ⊕ 61 *         |                            |                   |
| CQE .....                  | 18 poles + ⊕ 81 *         |                            |                   |
| CSH .....                  | 10 poles + ⊕ 89 *         |                            |                   |
| CCE .....                  | 10 poles + ⊕ 90 *         |                            |                   |
| CNE, CSE, JONE, JCSE ..... | 10 poles + ⊕ 97 and 107 * |                            |                   |
| CSS .....                  | 10 poles + ⊕ 119 *        |                            |                   |
| CTE, CTSE **) .....        | 10 poles + ⊕ 127 *        |                            |                   |
| CMSE .....                 | 3+2 (aux) poles + ⊕ 135 * |                            |                   |
| CMCE .....                 | 3+2 (aux) poles + ⊕ 134 * |                            |                   |
| CX .....                   | 8/24 poles + ⊕ 151 *      |                            |                   |
| MIXO .....                 | 3 modules 160+195 *       |                            |                   |

insert centre distance: 57 x 27 mm

\* refer to catalogue page CN.12

| description  | part no.          | entry     | part no.          | entry     |
|--|-------------------|-----------|-------------------|-----------|
|  |                   | M         |                   | M         |
| bulkhead mounting housing, with 2 levers                   | <b>CHIN 10</b>    |           |                   |           |
| surface mounting housing, high construction, with 2 levers | <b>MAPN 10.32</b> | <b>32</b> |                   |           |
| with pegs, side entry                                      |                   |           | <b>MHON 10.25</b> | <b>25</b> |
| with pegs, side entry, high construction                   |                   |           | <b>MFON 10.32</b> | <b>32</b> |
| with pegs, top entry                                       |                   |           | <b>MHVN 10.25</b> | <b>25</b> |
| with pegs, top entry, high construction                    |                   |           | <b>MFVN 10.32</b> | <b>32</b> |

\*\*) only in the CHIN 10 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

**CHIN 10**

**MAPN 10.32**

dimensions in mm

**MFON 10.32**

**MFVN 10.32**

**MHON 10.25**

**MHVN 10.25**

**6**

## Notes

Dimensions shown in mm are not binding and may be changed without notice.