Part number

MSLZ 24 IV





Complete connector, CSZ series, composed of 2 spring terminal connection inserts with 24 poles + PE, and bulkhead mounting housing with 1 lever and hood with top cable entry

Product description	
Product type	Complete connector
Series	CSZ
Connection type	Spring terminal connection
Size	Size 104.27
N. of poles	24 poles + 🕒
Cable entry	M32
Specification	Bulkhead mounting housing with 1 lever and hood with top cable entry
Technical data	
Current	16 A
Voltage	500 V
Rated impulse withstand voltage	6 kV
Pollution degree	3
Wire cross-section	0,50 mm ² - 2,50 mm ²
AWG size	20 - 14
Contact type	Turned silver plated
IP degree of protection	IP65 / IP66 / IP69
Further technical details	
Weight	590,00 g

Material properties	
Colour	RAL 7040 grey
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	A54fce24-f9c5-479f-a7e4-adb75fec7abe
Approvals / Standards	
Reference standard	EN 61984:2009-06
Certifications	EAC
General ordering information	
EAN13 code	8015747120401
Packaging Information	
Packaging length	315,00 mm
Packaging height	230,00 mm
Packaging width	300,00 mm
Packaging weight	11,82 kg
Packaging volume	21,74 dm³
Packaging description	Carton box
Packaging quantity	20 Pcs
Packaging EAN code	8015747121378
Sub-packaging length	302,00 mm
Sub-packaging height	41,00 mm
Sub-packaging width	155,00 mm
Sub-packaging weight	2,96 kg
Sub-packaging volume	1,92 dm³
Sub-packaging description	Carton tray
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747121385

Part number

MSLZ 24 IV



Notes

Dimensions shown in mm are not binding and may be changed without notice.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.