

Part number

MSZ 24 IV



Complete connector, CSZ series, composed of 2 spring terminal connection inserts with 24 poles + PE, and bulkhead mounting housing with 2 levers and hood with top cable entry

Product description		Material properties	
Product type	Complete connector	Colour	RAL 7040 grey
Series	CSZ		Compliant with exemption
Connection type	Spring terminal connection	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Size	Size "104.27"	China RoHs - EFUP	50
N. of poles	24 poles + 	REACH SVHC substances	Yes
Cable entry	M32		Lead
Specification	Bulkhead mounting housing with 2 levers and hood with top cable entry	SCIP number	A54fce24-f9c5-479f-a7e4-adb75fec7abe
Technical data		Approvals / Standards	
Current	16 A	Reference standard	EN 61984:2009-06
Voltage	500 V	Certifications	EAC
Rated impulse withstand voltage	6 kV	General ordering information	
Pollution degree	3	EAN13 code	8015747120364
Wire cross-section	0,50 mm² - 2,50 mm²	Packaging Information	
AWG size	20 - 14	Packaging length	315,00 mm
Contact type	Turned silver plated	Packaging height	230,00 mm
IP degree of protection	IP65 / IP66 / IP69	Packaging width	300,00 mm
Further technical details		Packaging weight	11,94 kg
Weight	597,00 g	Packaging volume	21,74 dm³
		Packaging description	Carton box
		Packaging quantity	20 Pcs
		Packaging EAN code	8015747120753
		Sub-packaging length	302,00 mm
		Sub-packaging height	41,00 mm
		Sub-packaging width	155,00 mm
		Sub-packaging weight	2,99 kg
		Sub-packaging volume	1,92 dm³
		Sub-packaging description	Carton tray
		Sub-packaging quantity	5 Pcs
		Sub-packaging EAN barcode	8015747120760

Part number

MSZ 24 IV



Notes

Dimensions shown in mm are not binding and may be changed without notice.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
