

Part number

CHIN 06 L



Bulkhead mounting housing, LS-TYPE series,
with 1 lever, size "44.27"

Product description

Product type	Bulkhead mounting housing
Series	LS-TYPE
Closing type	With 1 lever
Size	Size 44.27
Cable entry	Without cable entry

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	65,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747161596
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Packaging length	255,00 mm
Packaging height	195,00 mm
Packaging width	245,00 mm
Packaging weight	2,60 kg
Packaging volume	12,18 dm ³
Packaging description	Carton box
Packaging quantity	40 Pcs
Packaging EAN code	8015747187565
Sub-packaging weight	0,33 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187572

Part number

CHIN 06 L



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures

size "44.27"

LS-TYPE version

inserts:

CDD	24 poles + Ⓢ	59 *
CQE	10 poles + Ⓢ	80 *
CSH	6 poles + Ⓢ	88 *
CCE	6 poles + Ⓢ	94 *
CNE, CSE, JONE, JCSE	6 poles + Ⓢ 95 and 106 *	118 *
CSS	6 poles + Ⓢ	126 *
CTE, CTSE **)	6 poles + Ⓢ	126 *
MIXO	2 modules	160+195 *

insert centre distance: 44 x 27 mm

* refer to catalogue page CN.12

housings with single lever

hoods with 2 pegs

part no.

entry

M

part no.

entry

M

description

bulkhead mounting housing, with lever

surface mounting housing, high construction, with lever

with pegs, side entry

with pegs, side entry, high construction

with pegs, top entry

with pegs, top entry, high construction

part no.

CHIN 06 L

MAPN 06 L32

32

part no.

MHON 06 L25

25

MFON 06 L25

25

MHVN 06 L25

25

MFVN 06 L25

25

**) only in the CHIN 06 L enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

IP65

dimensions shown are not binding and may be changed without notice

dimensions in mm

CHIN 06 L

MAPN 06 L32

dimensions in mm

MFON 06 L25

MFVN 06 L25

MHON 06 L25

MHVN 06 L25

4

Notes