

Part number

# CAVW 24.221



Hood, W-TYPE series, with 4 pegs, Pg21 x 2 double top cable entry, size "104.27", high construction

| Product description                    |                                              | Material properties       |                                                       |
|----------------------------------------|----------------------------------------------|---------------------------|-------------------------------------------------------|
| Product type                           | Hood                                         | Other materials           | Gasket: FKM                                           |
| Series                                 | W-TYPE                                       | Colour                    | RAL 9005 black                                        |
| Closing type                           | With 4 pegs                                  | RoHs conformity           | Compliant with exemption                              |
| Size                                   | Size "104.27"                                |                           | 6(c): copper alloy containing up to 4% lead by weight |
| Cable entry                            | Double top cable entry with adapter Pg21 x 2 |                           |                                                       |
| Specification                          | High construction                            | China RoHs - EFUP         | 50                                                    |
| Technical data                         |                                              | REACH SVHC substances     | Yes<br>Lead                                           |
| IP degree of protection                | IP65 / IP66 / IP69                           | SCIP number               | 15deaf78-e939-4401-a0b0-e2228ca32a03                  |
| Further technical details              |                                              | Approvals / Standards     |                                                       |
| Operating temperature range (min, max) | -40°C...+125°C                               | Certifications            | DNV, BV                                               |
|                                        |                                              | UL                        | ECBT2                                                 |
|                                        |                                              | cUL                       | ECBT8                                                 |
| General ordering information           |                                              |                           |                                                       |
|                                        |                                              | EAN13 code                | 8015747011099                                         |
| Packaging Information                  |                                              |                           |                                                       |
|                                        |                                              | Sub-packaging description | Plastic packaging                                     |
|                                        |                                              | Sub-packaging quantity    | 1 Pcs                                                 |
|                                        |                                              | Sub-packaging EAN barcode | 8015747011105                                         |