

Part number

CC 2.5 AN



Male crimp contact, CC series, 16 A, turned silver plated, wire cross section 2,5 mm², AWG 14, advanced opening


Product description		Material properties	
Product type	Crimp contact	Main material	Copper alloy
Series	CC		Compliant with exemption
Gender	Male	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Specification	Advanced opening	China RoHs - EFUP	50
Technical data		REACH SVHC substances	Yes
Current	16 A		Lead
Wire cross-section	2,50 mm ²	SCIP number	C0979fba-9907-458f-a94a-db781440f273
AWG size	14	Approvals / Standards	
Contact type	Turned silver plated	Certifications	CSA, EAC
Further technical details		UL	ECBT2
Weight	1,30 g	General ordering information	
Conductors stripping length	7,5 mm	EAN13 code	8015747011259
		eCl@ss 8.1	27440204
		ETIM 7.0	EC000796
Packaging Information			
		Sub-packaging length	50,00 mm
		Sub-packaging height	44,00 mm
		Sub-packaging width	50,00 mm
		Sub-packaging weight	0,07 kg
		Sub-packaging volume	0,11 dm ³
		Sub-packaging description	Plastic box
		Sub-packaging quantity	50 Pcs
		Sub-packaging EAN barcode	8015747011266

Part number

CC 2.5 AN



Catalogue drawings



CCF, CCM and CC..AN contacts

conductor section mm ²	conductor slot ø A (mm)	conductors stripping length (mm)
0,14-0,37	0,9	7,5
0,5	1,1	7,5
0,75	1,3	7,5
1,0	1,45	7,5
1,5	1,8	7,5
2,5	2,2	7,5
3	2,55	7,5
4	2,85	7,5