

Part number

COB 24 CMS



Insulating insert carrier enclosure for mobile mounting, COB panel supports series, side cable entry with cable clamp, for inserts with 104 x 27 mm screw fixing centre distance

Product description		Material properties	
Product type	Insulating insert carrier enclosure for mobile mounting	Colour	RAL 7032 grey
Series	COB panel supports	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Cable entry	Side cable entry with cable clamp	China RoHs - EFUP	50
Specification	For inserts with 104 x 27 mm screw fixing centre distance	REACH SVHC substances	Yes Lead
Technical data		SCIP number	B008b8e4-629e-4e70-ab7d-b3b67464925d
IP degree of protection	IP20	Approvals / Standards	
Further technical details		Certifications	DNV, BV
Weight	95,00 g	UL	ECBT2
Operating temperature range (min, max)	-40°C...+125°C	cUL	ECBT8
General ordering information			
EAN13 code		8015747036672	
eCl@ss 8.1		27440202	
ETIM 7.0		EC000437	
Packaging Information			
Packaging length		225,00 mm	
Packaging height		130,00 mm	
Packaging width		150,00 mm	
Packaging weight		0,95 kg	
Packaging volume		4,39 dm³	
Packaging description		Carton box	
Packaging quantity		10 Pcs	
Packaging EAN code		8015747036689	
Sub-packaging weight		0,10 kg	
Sub-packaging description		Carton tray	
Sub-packaging quantity		1 Pcs	
Sub-packaging EAN barcode		8015747036696	

Part number

COB 24 CMS



Catalogue drawings

COB..CMS

