

Part number

CCMD 4.0



Male crimp contact, CC series, 16 A, turned gold plated, wire cross section 4 mm², AWG 12


Product description		Material properties	
Product type	Crimp contact	Main material	Copper alloy
Series	CC		Compliant with exemption
Gender	Male	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Technical data		China RoHs - EFUP	50
Current	16 A	REACH SVHC substances	Yes
Wire cross-section	4,00 mm ²		Lead
AWG size	12	SCIP number	C0979fba-9907-458f-a94a-db781440f273
Contact type	Turned gold plated	Approvals / Standards	
Further technical details		Certifications	CSA, EAC
Weight	1,30 g	UL	ECBT2
Conductors stripping length	7,5 mm	General ordering information	
		EAN13 code	8015747012669
		eCl@ss 8.1	27440204
		ETIM 7.0	EC000796
Packaging Information			
		Packaging length	112,00 mm
		Packaging height	95,00 mm
		Packaging width	117,00 mm
		Packaging weight	1,25 kg
		Packaging volume	1,24 dm ³
		Packaging description	Carton box
		Packaging quantity	800 Pcs
		Packaging EAN code	8015747207355
		Sub-packaging length	50,00 mm
		Sub-packaging height	44,00 mm
		Sub-packaging width	50,00 mm
		Sub-packaging weight	0,16 kg
		Sub-packaging volume	0,11 dm ³
		Sub-packaging description	Plastic box
		Sub-packaging quantity	100 Pcs
		Sub-packaging EAN barcode	8015747012676

Part number

CCMD 4.0



Catalogue drawings



CCF, CCM and CC..AN contacts

conductor section mm^2	conductor slot $\varnothing A$ (mm)	conductors stripping length (mm)
0,14-0,37	0,9	7,5
0,5	1,1	7,5
0,75	1,3	7,5
1,0	1,45	7,5
1,5	1,8	7,5
2,5	2,2	7,5
3	2,55	7,5
4	2,85	7,5

Notes

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
