

Codice articolo

MFON 06 L25



Custodia mobile, serie LS-TYPE, con 2 piolini, ingresso cavo orizzontale M25 senza adattatore, grandezza "44.27", alta

Descrizione prodotto

Tipo prodotto	Custodia mobile
Serie	LS-TYPE
Tipo chiusura	Con 2 piolini
Grandezza	Grandezza "44.27"
Ingresso cavo	Ingresso cavo orizzontale M25
Specifica	Alta

Dati tecnici

Grado di protezione IP	IP65
-------------------------------	------

Ulteriori dettagli tecnici

Peso	0,50 g
Temperature di esercizio (min, max)	-40°C...+125°C

Proprietà dei materiali

Colore	Nero RAL 9005
Conformità RoHs	Conforme
China RoHs - EFUP	E
Sostanze REACH SVHC	No

Approvazioni / Normative

Certificazioni	DNV, BV
UL	ECBT2
cUL	ECBT8

Informazioni commerciali

Codice EAN13	8015747163156
Classificazione ecl@ss	27440202
Classificazione ETIM	EC000437

Caratteristiche imballaggio


Lunghezza imballo	175,00 mm
Altezza imballo	195,00 mm
Profondità imballo	260,00 mm
Volume imballo	8,87 dm ³
Descrizione imballo	Scatola cartone
Quantità imballo	20 pz
Codice EAN13 imballo	8015747187725
Descrizione sottoimballo	Termoretraibile
Quantità sottoimballo	5 pz
Codice EAN13 sottoimballo	8015747187695

Codice articolo

MFON 06 L25



Disegni da catalogo



Disegni da catalogo

CH..N - MA, MF..N enclosures

size "44.27"

LS-TYPE version

inserts:

CDD	24 poles + Ⓢ	59 *
CQE	10 poles + Ⓢ	80 *
CSH	6 poles + Ⓢ	88 *
CCE	6 poles + Ⓢ	94 *
CNE, CSE, JONE, JCSE	6 poles + Ⓢ 95 and 106 *	118 *
CSS	6 poles + Ⓢ	126 *
CTE, CTSE **)	6 poles + Ⓢ	126 *
MIXO	2 modules	160+195 *

insert centre distance: 44 x 27 mm

* refer to catalogue page CN.12

housings with single lever

hoods with 2 pegs

description	part no.	entry	part no.	entry
bulkhead mounting housing, with lever	CHIN 06 L	M		
surface mounting housing, high construction, with lever	MAPN 06 L32	32		
with pegs, side entry			MHON 06 L25	25
with pegs, side entry, high construction			MFON 06 L25	25
with pegs, top entry			MHVN 06 L25	25
with pegs, top entry, high construction			MFVN 06 L25	25

**) only in the CHIN 06 L enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

IP65

IP65

dimensions shown are not binding and may be changed without notice

dimensions in mm

CHIN 06 L

MAPN 06 L32

dimensions in mm

MFON 06 L25

MFVN 06 L25

MHON 06 L25

MHVN 06 L25

4

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.