

Codice articolo

MHVN 24 G32



Custodia mobile, serie LS-TYPE, con 2 leve,
ingresso cavo verticale M32, grandezza
"104.27"


Descrizione prodotto		Proprietà dei materiali	
Tipo prodotto	Custodia mobile	Altri materiali	Leva: Poliammide (PA) Guarnizione: NBR
Serie	LS-TYPE	Colore	Nero RAL 9005
Tipo chiusura	Con 2 leve	Conformità RoHs	Conforme
Grandezza	Grandezza "104.27"	China RoHs - EFUP	E
Ingresso cavo	Ingresso cavo verticale M32	Sostanze REACH SVHC	No
Dati tecnici		Approvazioni / Normative	
Grado di protezione IP	IP65	Certificazioni	DNV, BV
Ulteriori dettagli tecnici		UL	ECBT2
Peso	248,00 g	cUL	ECBT8
Temperature di esercizio (min, max)	-40°C...+125°C	Informazioni commerciali	
		Codice EAN13	8015747194402
		Classificazione ecl@ss	27440202
		Classificazione ETIM	EC000437
Caratteristiche imballaggio			
		Peso sottoimballo	1,24 kg
		Descrizione sottoimballo	Termoretraibile
		Quantità sottoimballo	5 pz
		Codice EAN13 sottoimballo	8015747194419

Codice articolo

MHVN 24 G32



Disegni da catalogo



Disegni da catalogo

CH..N - MF..N enclosures

size "104.27"

LS-TYPE version

inserts:

CD	64 poles + @	51+53 *
CDD	108 poles + @	64+66 *
CQE	46 poles + @	83+85 *
CSH	24 poles + @	91+93 *
CCE	24 poles + @	100+104 *
CNE, CSE, JONE, JCSE	24 poles + @	101 and 109 *
CSS	24 poles + @	121+123 *
CMSE	10+2 (aux) poles + @	139 *
CMCE	10+2 (aux) poles + @	138 *
CX	4/6 poles + @	155 *
MIXO	6 modules	160+195 *

insert centre distance: 104 x 27 mm

* refer to catalogue page CN.12

hoods with 4 pegs

covers

description	part no.	entry M	part no.
with 2 levers and gasket, top entry	MHVN 24 G32	32	CHCN 24
with 2 levers and gasket, top entry, high construction	MFVN 24 G32	32	CHCN 24 G

covers with pegs

covers with 2 levers

dimensions in mm

MHVN 24 G32

MFVN 24 G32

dimensions in mm

CHCN 24

CHCN 24 G

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

IP65

dimensions shown are not binding and may be changed without notice

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.