

品番

MAPN 24.32



サーフェスマウントハウジング, LS-タイプ
シリーズ, 2レバー付, M32 ケーブルエントリー
, サイズ "104.27", ハイコンストラクション

製品説明

製品タイプ	サーフェスマウントハウジング
シリーズ	LS-タイプ
クロージングタイプ	2レバー付
サイズ	サイズ"104.27"
ケーブルエントリー	ケーブルエントリー付 M32
仕様	ハイコンストラクション

技術データ

IP 保護等級	IP65
---------	------

技術詳細

重さ	444,00 g
動作温度範囲 (最小・最大)	-40°C...+125°C

材料特性

その他の素材	レバー: ポリアミド (PA) ガスケット: NBR
カラー	RAL 9005

認証 / 規格

認証	DNV, BV
UL	ECBT2
cUL	ECBT8

ジェネラルオーダーリングインフォメーション

EAN13 コード	8015747163149
ecl@ss 分類	27440202
ETIM 分類	EC000437

パッケージ情報


パッケージ長さ	305,00 mm
パッケージ高さ	180,00 mm
パッケージ幅	275,00 mm
パッケージ重量	4,96 kg
パッケージ体積	15,10 dm ³
パッケージ 詳細	カートンボックス
パッケージ 数量	10 個
パッケージ EAN コード	8015747250207
サブパッケージ 重量	2,48 kg
サブパッケージ 詳細	プラスチック包装
サブパッケージ 数量	5 個
サブパッケージ EAN パーコード	8015747187671

品番

MAPN 24.32



カタログ図面



カタログ図面

CH..N - MA, MF..N enclosures

size "104.27"

LS-TYPE version

inserts:

CD	64 poles + @	51+53 *
CT, CTS **)	64 poles + @	57 *
CDD	108 poles + @	64+66 *
CDE	46 poles + @	83+85 *
CSH	24 poles + @	91+93 *
CCE	24 poles + @	100+104 *
CNE, CSE, JCNE, JCSE	24 poles + @	101 and 109 *
CSS	24 poles + @	122+123 *
CTE, CTSE **)	24 poles + @	129 *
CMSE	10+2 (aux) poles + @	139 *
CMCE	10+2 (aux) poles + @	138 *
CX	4/8 poles + @	155 *
MIXO	6 modules	160+195 *

insert centre distance: 104 x 27 mm

* refer to catalogue page CN.12

housings with double lever

hoods with 4 pegs

description	part no.	entry M	part no.	entry M
bulkhead mounting housing, with 2 levers	CHIN 24			
surface mounting housing, high construction, with 2 levers	MAPN 24.32	32		
with pegs, side entry			MHON 24.32	32
with pegs, side entry, high construction			MFON 24.32	32
with pegs, side entry			MHVN 24.32	32
with pegs, side entry, high construction			MFVN 24.32	32

** only in the CHIN 24 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

CHIN 24

MAPN 24.32

dimensions in mm

MFON 24.32

MFVN 24.32

MHON 24.32

MHVN 24.32

メモ

mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。