
品番

RSHM 10




製品説明	
製品タイプ	インサート
シリーズ	RSH
接続タイプ	SQUICH® 工具不要バネ式接続
性別	オス
極数	10極 + ⏚
サイズ	サイズ"57.27"
仕様	HNM-高嵌合回数対応
技術データ	
電流	16 A
電圧	500 V
定格インパルス耐電圧	6 kV
汚染度	3
UL/CSA に準拠した定格電圧	600 V
導体断面積	0,14 mm² - 2,50 mm²
AWG サイズ	26 - 14
コンタクトタイプ	切削コンタクト 金メッキ
IP 保護等級	エンクロージャなしの場合IP20 エンクロージャ有りの場合IP65/IP66/IP68/IP69
技術詳細	
EN 61984 に準拠した特性	16A 500V 6kV 3
機械寿命	≥ 10000
絶縁抵抗	≥ 10 GΩ
接触抵抗	≤ 3 mΩ
重さ	64,00 g
動作温度範囲（最小・最大）	-40°C...+125°C
メインコンタクト　導体被覆むき長さ	7 mm
UL 94 可燃性定格	V-0

材料特性	
主な素材	ポリカーボネート
その他の素材	銅合金
カラー	RAL 7032
SCIP番号	1a9c93ff-0445-4a16-81e3-1609ac5274d6
認証 / 規格	
認証	DNV, EAC
ジェネラルオーダリングインフォメーション	
EAN13 コード	8015747014960
ecl@ss 分類	27440205
ETIM 分類	EC000438
パッケージ情報	
パッケージ長さ	245,00 mm
パッケージ高さ	165,00 mm
パッケージ幅	215,00 mm
パッケージ重量	2,42 kg
パッケージ体積	8,69 dm³
パッケージ　詳細	カートンボックス
パッケージ　数量	30 個
パッケージ EAN コード	8015747015554
サブパッケージ 長さ	197,00 mm
サブパッケージ 高さ	44,00 mm
サブパッケージ 幅	113,00 mm
サブパッケージ 重量	0,40 kg
サブパッケージ 体積	0,98 dm³
サブパッケージ 詳細	カートントレイ
サブパッケージ 数量	5 個
サブパッケージ EAN バーコード	8015747015585


品番

RSHM 10

カタログ図面



ディレーティング曲線



メモ

California Proposition 65 Information

WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 Information

WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。