

品番

ZFU-CD



全自動圧着機, 自動ストリッピング機能付き,
10 A 及び 16 A 切削コンタクト用

製品説明		ジェネラルオーダリングインフォメーション	
製品タイプ	全自動圧着機	EAN13 コード	8015747100335
仕様	自動被覆剥き機能付き 10Aおよび16A切削コンタクト用	ecl@ss 分類	17130101
技術詳細		ETIM 分類	EC002778
重さ	10,00 g	パッケージ情報	
		パッケージ 詳細	プラスチック包装
		パッケージ 数量	1個
		パッケージ EAN コード	8015747280822

品番

ZFU-CD



カタログ図面

Technical specifications		Tools list	
Drive.....	electro-pneumatic	contacts	
Electric feeder.....	380V/50Hz	conductor section (mm ²)	0.34 0.5 0.75 1.0 1.5 2.5 3.5 0.75 1.0 1.5 2.5
Assembled power.....	1200VA	AWG (approximate)	22 20 18 16 14 12 10 20 18 16 14
Phase (on the system fiber module).....	2 x 2 A m.l	feeding technique	A B (F)
Air operating pressure.....	5.5 bar	loading tube	B
Air consumption.....	2.0 l/kg	wire holder	0.34 0.5-1.5 2.5 0.5-1.5 2.5
Feasible conductors in conformity with.....	IEC 60268 class G	stripping unit	20
Rated section.....	0.34-2.5 mm ² (20 AWG-14 AWG)	stripping blades	V-shaped blades V-shaped blades
Feeding length.....	52 mm	row blade apertures	0.5 mm / 1.0 mm 0.5 mm / 1.0 mm
Contact.....	30mm, turned	contact holder / pins	A (M) B
Contact breaker.....	See list of tools	contact holder / bushings	A (F) B
Feeding.....	Vibrating conveyor	contact stop	A B
Clamping form.....	40 mm		
Cycle time.....	0.5 s - 5 s		
Continuous sound level.....	70 dB (A)		
Dimensions (L x S x H).....	250 x 500 x 480 mm		
Color.....	Black, RAL 9010		
Weight.....	40 Kg		

Preset stripping and contact crimping programs	
conductor section (mm ²)	0.34 0.5 0.75 1.0 1.5 2.5 3.5 0.75 1.0 1.5 2.5
AWG (approximate)	22 20 18 16 14 12 10 20 18 16 14
Program number	1A 2A 3A 4A 5A 6A 7B 8B 9B 10B 11B
stripping position (mm)	0.75 1.00 1.25 1.50 1.75 2.00 2.25 2.50 2.75 3.00 3.25
stripping position	1.30 1.35 1.40 1.50 1.55 1.60 1.65 1.70 1.75 1.80 1.85

Supplied with the following accessories:

- 1 vibrating conveyor feeder bowl for CD contact series
- 1 vibrating conveyor feeder bowl for male CD contact series
- 1 vibrating conveyor feeder bowl for female CD contact series
- 1 feeder tube (contact passage from vibrating conveyor to machine) for CD contact series
- 1 feeder tube (contact passage from vibrating conveyor to machine) for CC contact series
- 1 contact holder (in crimping position) for male CD contact series
- 1 contact holder (in crimping position) for female CD contact series
- 1 contact holder (in crimping position) for CC contact series
- 1 contact stop for CD contact series
- 1 contact stop for CC contact series
- 1 wire holder for 0.34 mm² cables
- 1 wire holder for 0.5 to 1.5 mm² cables
- 1 wire holder for 2.5 mm² cables
- 1 100 / 100 GSP control gauge
- 1 Allen wrench for setup operations
- 1 set of spacers to regulate the stripping length
- 1 removal tool to extract contacts from the crimping chamber

メモ

mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。