

Part number

# JSHM 16 N



Male insert, JSH series, SQUICH® spring terminal connection without tools, 16 poles + PE (17-32), 16 A 500 V 6 kV 3, size "77.62"

| Product description                    |                                                                                              |
|----------------------------------------|----------------------------------------------------------------------------------------------|
| Product type                           | Insert                                                                                       |
| Series                                 | JSH                                                                                          |
| Connection type                        | SQUICH® spring terminal connection without tools                                             |
| Gender                                 | Male                                                                                         |
| N. of poles                            | 32 poles +  |
| Size                                   | Size "77.62"                                                                                 |
| Technical data                         |                                                                                              |
| Current                                | 16 A                                                                                         |
| Voltage                                | 500 V                                                                                        |
| Pollution degree                       | 3                                                                                            |
| Rated voltage according to UL/CSA      | 600V                                                                                         |
| Wire cross-section                     | 0,14 mm² - 2,50 mm²                                                                          |
| AWG size                               | 26 - 14                                                                                      |
| Contact type                           | Turned tin plated                                                                            |
| Pole numbering system                  | 17-32                                                                                        |
| IP degree of protection                | IP20 without enclosure, IP65/IP66 with enclosure                                             |
| Further technical details              |                                                                                              |
| Characteristics according to EN 61984  | 16A 500V 6kV 3; 16A 400/690V 6kV 2                                                           |
| Mating cycles                          | ≥ 200                                                                                        |
| Insulation resistance                  | ≥ 10 GΩ                                                                                      |
| Weight                                 | 85,00 g                                                                                      |
| Operating temperature range (min, max) | -40 °C ... +125 °C                                                                           |
| UL 94 flammability rating              | V-0                                                                                          |

| Material properties          |                                                                                |
|------------------------------|--------------------------------------------------------------------------------|
| Main material                | Polycarbonate (PC)                                                             |
| Other materials              | Contacts: copper alloy                                                         |
| Colour                       | RAL 7035 grey                                                                  |
| RoHs conformity              | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP            | 50                                                                             |
| REACH SVHC substances        | Yes<br>Lead                                                                    |
| SCIP number                  | 1a9c93ff-0445-4a16-81e3-1609ac5274d6                                           |
| Approvals / Standards        |                                                                                |
| Reference standard           | EN 61984:2009-06                                                               |
| Certifications               | CSA, CQC, DNV, BV, EAC                                                         |
| General ordering information |                                                                                |
| EAN13 code                   | 8015747090742                                                                  |
| Packaging Information        |                                                                                |
| Packaging length             | 245,00 mm                                                                      |
| Packaging height             | 165,00 mm                                                                      |
| Packaging width              | 215,00 mm                                                                      |
| Packaging weight             | 3,01 kg                                                                        |
| Packaging volume             | 8,69 dm³                                                                       |
| Packaging description        | Carton box                                                                     |
| Packaging quantity           | 30 Pcs                                                                         |
| Packaging EAN code           | 8015747090759                                                                  |
| Sub-packaging length         | 197,00 mm                                                                      |
| Sub-packaging height         | 44,00 mm                                                                       |
| Sub-packaging width          | 113,00 mm                                                                      |
| Sub-packaging weight         | 0,50 kg                                                                        |
| Sub-packaging volume         | 0,98 dm³                                                                       |
| Sub-packaging description    | Carton tray                                                                    |
| Sub-packaging quantity       | 5 Pcs                                                                          |
| Sub-packaging EAN barcode    | 8015747090766                                                                  |