

Part number

# MLAV 24 G25



Hood, IL-BRID series, with 2 levers, M25 top cable entry, size "104.27", high construction

| Product description                    |                                     | Material properties          |                                                                                   |
|----------------------------------------|-------------------------------------|------------------------------|-----------------------------------------------------------------------------------|
| Product type                           | Hood                                | Other materials              | Lever: Polyamide (PA) and Stainless steel core<br>Gasket NBR                      |
| Series                                 | IL-BRID                             | Colour                       | RAL 7040 grey                                                                     |
| Closing type                           | With 2 levers                       | RoHs conformity              | Compliant with exemption<br>6(c): copper alloy containing up to 4% lead by weight |
| Size                                   | Size "104.27"                       | China RoHs - EFUP            | 50                                                                                |
| Cable entry                            | Top cable entry with adapter<br>M25 | REACH SVHC substances        | Yes<br>Lead                                                                       |
| Specification                          | High construction                   | Approvals / Standards        |                                                                                   |
| Technical data                         |                                     | Certifications               | DNV                                                                               |
| IP degree of protection                | IP65 / IP66 / IP69                  | General ordering information |                                                                                   |
| Further technical details              |                                     | EAN13 code                   | 8015747288088                                                                     |
| Operating temperature range (min, max) | -40°C...+125°C                      | eCl@ss 8.1                   | 27440202                                                                          |
|                                        |                                     | ETIM 7.0                     | EC000437                                                                          |
|                                        |                                     | Packaging Information        |                                                                                   |
|                                        |                                     | Sub-packaging description    | Plastic packaging                                                                 |
|                                        |                                     | Sub-packaging quantity       | 5 Pcs                                                                             |
|                                        |                                     | Sub-packaging EAN barcode    | 8015747297066                                                                     |

Part number

# MLAV 24 G25



Catalogue drawings

