

Part number

RCEF 16



Female insert, RCE series, crimp connection, 16 poles + PE, 16 A 500 V 6 kV 3, size "77.27", HNM - High Number of Matings version

Product description	
Product type	Insert
Series	RCE
Connection type	Crimp connection
Gender	Female
N. of poles	16 poles + 
Size	Size 77.27
Specification	HNM - High Number of Matings version
Technical data	
Current	16 A
Voltage	500 V
Rated impulse withstand voltage	6 kV
Pollution degree	3
Rated voltage according to UL/CSA	600 V
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure
Further technical details	
Mating cycles	≥ 10000
Insulation resistance	≥ 10 GΩ
Contact resistance	≤ 1 mΩ
Weight	0,33 g
Operating temperature range (min, max)	-40 °C ... +125 °C
UL 94 flammability rating	V-0


Material properties	
Main material	Polycarbonate (PC)
Colour	RAL 7032 grey
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No
Approvals / Standards	
Certifications	DNV, BV, EAC
UL	ECBT2
General ordering information	
EAN13 code	8015747253635
eCl@ss 8.1	27440205
ETIM 7.0	EC000438
Packaging Information	
Packaging length	230,00 mm
Packaging height	110,00 mm
Packaging width	180,00 mm
Packaging volume	4,55 dm³
Packaging description	Carton box
Packaging quantity	30 Pcs
Packaging EAN code	8015747253642
Sub-packaging length	87,00 mm
Sub-packaging height	36,00 mm
Sub-packaging width	180,00 mm
Sub-packaging volume	0,56 dm³
Sub-packaging description	Carton tray
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747253659

Part number

RCEF 16



Catalogue drawings



Derating curves

