

Part number

RQF 05



Female insert, CQ series, crimp connection, 5 poles + PE, 16 A 230/400 V 4 kV 3, size "21.21", HNM - High Number of Matings series


Product description		Material properties	
Product type	Insert	Main material	Polycarbonate (PC)
Series	CQ	Colour	RAL 7032 grey
Connection type	Crimp connection		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Gender	Female	RoHs conformity	
N. of poles	5 poles + 	China RoHs - EFUP	50
Size	Size "21.21"	REACH SVHC substances	Yes
Specification	HNM - High Number of Matings version	Lead	
Technical data		SCIP number	1a9c93ff-0445-4a16-81e3-1609ac5274d6
Current	16 A	Approvals / Standards	
Voltage	230 - 400 V	Certifications	DNV
Rated impulse withstand voltage	4 kV	General ordering information	
Pollution degree	3	EAN13 code	8015747174039
Rated voltage according to UL/CSA	600 V	eCl@ss 8.1	27440205
IP degree of protection	IP20 without enclosure, IP44/IP66/IP67/IP68/IP69 with enclosure	ETIM 7.0	EC000438
Further technical details		Packaging Information	
Characteristics according to EN 61984	16A 230/400V 4kV 3; 16A 320/500V 4kV 2	Packaging length	220,00 mm
Mating cycles	≥ 5000	Packaging height	130,00 mm
Insulation resistance	≥ 10 GΩ	Packaging width	240,00 mm
Contact resistance	≤ 1 mΩ	Packaging weight	3,36 kg
Weight	14,00 g	Packaging volume	6,86 dm ³
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging description	Carton box
UL 94 flammability rating	V-0	Packaging quantity	200 Pcs
Tightening torque for PE connection	M3: 0,5 Nm; 4,4 lb.in (0,5 x 3 mm)	Packaging EAN code	8015747174053
Tightening torque for fixing screws	M3: 0,5 Nm; 4,4 lb.in (Ph1 or 0,8 x 5,5 mm)	Sub-packaging weight	0,02 kg
		Sub-packaging description	Plastic bag
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747140089

Part number

RQF 05



Catalogue drawings



Derating curves

RQ 05 poles connector inserts
Maximum current load derating diagram

