

Part number

CX7MA 16 XFP



Male crimp contact, CX7 series, 70 A, turned silver plated, wire cross section 16 mm², AWG 6 - 5, extra-flexible Class 6 conductor, finger-proof version

Product description	
Product type	Crimp contact
Series	CX7
Gender	Male
Specification	Finger-proof version
Technical data	
Current	70 A
Wire cross-section	16,00 mm ²
AWG size	6 - 5
Contact type	Turned silver plated
Further technical details	
Mating cycles	≥ 500
Contact resistance	≤ 0,5 mΩ
Operating temperature range (min, max)	-40°C ... +125°C
Conductors stripping length	15 mm

Material properties	
Main material	Copper alloy
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	C0979fba-9907-458f-a94a-db781440f273
Approvals / Standards	
Certifications	CSA, EAC
UL	ECBT2
cUL	ECBT8
General ordering information	
EAN13 code	8015747183758
eCl@ss 8.1	27440204
ETIM 7.0	EC000796
Packaging Information	
Sub-packaging length	50,00 mm
Sub-packaging height	44,00 mm
Sub-packaging width	50,00 mm
Sub-packaging volume	0,11 dm ³
Sub-packaging description	Plastic box
Sub-packaging quantity	16 Pcs
Sub-packaging EAN barcode	8015747279208

Part number

CX7MA 16 XFP



Catalogue drawings

