

Part number

MFVN 10 G32



Hood, LS-TYPE series, with 2 levers, M32 top cable entry without adapter, size "57.27", high construction


Product description		Material properties	
Product type	Hood	Colour	RAL 9005 black
Series	LS-TYPE	RoHs conformity	Compliant
Closing type	With 2 levers	China RoHs - EFUP	E
Size	Size 57.27	REACH SVHC substances	No
Cable entry	Top cable entry M32	Approvals / Standards	
Specification	High construction	Certifications	DNV, BV
Technical data		UL	ECBT2
IP degree of protection	IP65	cUL	ECBT8
Further technical details		General ordering information	
Weight	310,00 g	EAN13 code	8015747187404
Operating temperature range (min, max)	-40°C...+125°C	eCl@ss 8.1	27440202
		ETIM 7.0	EC000437
		Packaging Information	
		Sub-packaging weight	1,55 kg
		Sub-packaging description	Plastic packaging
		Sub-packaging quantity	5 Pcs
		Sub-packaging EAN barcode	8015747188166

Part number

MFVN 10 G32



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures

size "57.27"

LS-TYPE version

inserts:

CDD	42 poles + @	61 *
CQE	18 poles + @	81 *
CSH	10 poles + @	89 *
CCE	10 poles + @	90 *
CNE, CSE, JONE, JCSE	10 poles + @ 97 and 107 *	
CSS	10 poles + @	119 *
CMSE	3+2 (aux) poles + @	135 *
CMCE	3+2 (aux) poles + @	134 *
CX	8/24 poles + @	151 *
MIXO	3 modules	160+195 *

insert centre distance: 57 x 27 mm

* refer to catalogue page CN.12

hoods with 4 pegs

covers

description	part no.	entry M	part no.
with 2 levers and gasket, top entry	MHVN 10 G25	25	CHCN 10
with 2 levers and gasket, top entry, high construction	MFVN 10 G32	32	CHCN 10 G

covers with pegs

covers with 2 levers

dimensions in mm

MHVN 10 G25

MFVN 10 G32

dimensions in mm

CHCN 10

CHCN 10 G

- kiln powder coating with RAL 9005 black epoxy polyester powder

- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

IP65

dimensions shown are not binding and may be changed without notice

7