

Part number

CDSHF 42 N



Female insert, CDSH series, SQUICH® spring terminal connection without tools, 42 poles + PE (43-84), 10 A 400 V 6 kV 3, size "104.62"

Product description		Material properties	
Product type	Insert	Main material	Polycarbonate (PC)
Series	CDSH	Other materials	Contacts: copper alloy
Connection type	SQUICH® spring terminal connection without tools	Colour	RAL 7032 grey
Gender	Female	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	84 poles + 	China RoHs - EFUP	50
Size	Size "104.62"	REACH SVHC substances	Yes Lead
Technical data		SCIP number	1a9c93ff-0445-4a16-81e3-1609ac5274d6
Current	10 A	Approvals / Standards	
Voltage	400 V	Reference standard	EN 61984:2009-06
Rated impulse withstand voltage	6 kV	Certifications	DNV, BV, EAC, CQC
Pollution degree	3	UL	ECBT2
Rated voltage according to UL/CSA	600 V	cUL	ECBT8
Wire cross-section	0,14 mm² - 2,50 mm²	General ordering information	
AWG size	26 - 14	EAN13 code	8015747229951
Contact type	Turned silver plated	eCl@ss 8.1	27440205
Pole numbering system	43-84	ETIM 7.0	EC000438
IP degree of protection	IP20 without enclosure, IP65/IP66 with enclosure	Packaging Information	
Further technical details		Packaging length	245,00 mm
Mating cycles	≥ 500	Packaging height	165,00 mm
Insulation resistance	≥ 10 GΩ	Packaging width	215,00 mm
Contact resistance	≤ 3 mΩ	Packaging weight	4,68 kg
Weight	141,50 g	Packaging volume	8,69 dm³
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging description	Carton box
UL 94 flammability rating	V-0	Packaging quantity	30 Pcs
		Packaging EAN code	8015747230018
		Sub-packaging length	197,00 mm
		Sub-packaging height	55,00 mm
		Sub-packaging width	113,00 mm
		Sub-packaging weight	0,78 kg
		Sub-packaging volume	1,22 dm³
		Sub-packaging description	Carton tray
		Sub-packaging quantity	5 Pcs
		Sub-packaging EAN barcode	8015747230025