



# Part number

# CXL PF



## Brief description:

female insert , 2 pole fibre optics + 4 poles + PE optional, crimp connections, 10A 25V, 0,8kV, 3, size "21.21", CLASS insert series

Product description		Approvals / Standards	
<b>Model</b>	female insert	<b>Reference standard</b>	EN 61984:2009-06
<b>Version</b>	crimp connections	<b>Quality mark</b>	 DNV GL, BV
<b>Series</b>	DESINA	<b>Conformity</b>	Not applicable
<b>Product type</b>	for female contacts 10A	General ordering information	
<b>Style</b>	inserts for portable enclosures with: 4 + 1 crimp contacts (not included CDF and CDM series) + 2 snap on or HCS fibre optic contacts (not included)	<b>EAN13 code</b>	8015747127110
<b>Family</b>	CLASS inserts	<b>Tariff number</b>	85369095
<b>Size</b>	size "21.21"	<b>Country of origin</b>	Made in EU (IT)
<b>N. of poles</b>	2 pole fibre optics + 4 poles +  optional	<b>ETIM classification</b>	EC000438
Technical data		Packaging Information	
<b>Current</b>	10 A	<b>Sub-packaging description</b>	Plastic bag
<b>Voltage</b>	25 V	<b>Sub-packaging quantity</b>	1 Pcs
<b>Rated impulse withstand voltage</b>	0,8 kV	<b>Sub-packaging EAN barcode</b>	8015747127509
<b>Pollution degree</b>	3		
<b>Operating temperature range (min, max)</b>	-40°C...+70°C		
<b>Mating cycles</b>	≥ 500		
<b>IP degree of protection</b>	IP20 without enclosure, IP65/IP67 with enclosure		
Further technical details			
<b>Characteristics according to EN 61984</b>	10A 250V 4kV 3; 10A 230/400V 4kV 2		
<b>Insulation resistance</b>	≥ 10 GΩ		
<b>Contact resistance</b>	≤ 3 mΩ		
<b>Rated voltage according to UL/CSA</b>	600 V		
<b>UL 94 flammability rating</b>	V-0		
<b>Weight</b>	12,00 g		