

PVVA2.E506437 - Multi-point Interconnection Power Cable Assemblies for Industrial Machinery - Component

Multi-point Interconnection Power Cable Assemblies for Industrial Machinery - Component

ILME SPA

Via Marco Antonio
Colonna 9
Milano, Mi 20149 Italy



E506437

**Short-circuit-current Rating
Overcurrent Protection**

Model/ Cat. No.	No. of Poles	Con- duc tor Size, AWG	Cur- rent, A	Volt- age, V	Dis- con- nect Use	Env Rating	IP Rating	Fuse Size — Class/Max Amp Rating						Circuit Breaker Size		SCCR, RMS Sym, kA	Volts Max, V		
								J	T	L	RK1	RK5	G	CC	Mfr			Type	Max Amp
Male and female power inserts																			
CNE	6, 10, 16, 24	12- 14 STR	11.5	600 V ac/dc	-	-	-	-	-	-	-	15.0	-	-	-	-	-	5	600 V ac
CSH	6, 10, 16, 24	14 STR	11.5	600 V ac/dc	-	-	-	-	-	-	-	15.0	-	-	-	-	-	5	600 V ac
CCE	6, 10, 16, 24	14 STR	11.0	600 V ac/dc	-	-	-	-	-	-	-	15.0	-	-	-	-	-	5	600 V ac
CQ 05	5	12 STR	15.5	600 V ac/dc	-	-	-	-	-	-	-	20.0	-	-	-	-	-	5	600 V ac
CQ 05	5	14 STR	15.5	600 V ac/dc	-	-	-	-	-	-	-	20.0	-	-	-	-	-	5	600 V ac
CQ 07	7	16 STR	8.0	600 V ac/dc	-	-	-	-	-	-	-	10.0	-	-	-	-	-	5	600 V ac
CQ 07	7	14 STR	13.0	600 V ac/dc	-	-	-	-	-	-	-	15.0	-	-	-	-	-	5	600 V ac

CQ 12	12	16 STR	8.0	600 V ac/dc	-	-	-	-	-	-	-	10.0	-	-	-	-	-	5	600 V ac
CQ 12	12	14 STR	13.0	600 V ac/dc	-	-	-	-	-	-	-	15.0	-	-	-	-	-	5	600 V ac
CQ 08	8	14 STR	12.0	600 V ac/dc	-	-	-	-	-	-	-	15.0	-	-	-	-	-	5	600 V ac
CQ 08	8	12 STR	17.5	600 V ac/dc	-	-	-	-	-	-	-	20.0	-	-	-	-	-	5	600 V ac
CQ 04/2	4	12 STR	24.0	600 V ac/dc	-	-	-	-	-	-	-	25.0	-	-	-	-	-	5	600 V ac
CQ 04/2	4	10 STR	30.0	600 V ac/dc	-	-	-	-	-	-	-	30.0	-	-	-	-	-	5	600 V ac
CQ4 03	3	14 STR	23.0	600 V ac/dc	-	-	-	-	-	-	-	25.0	-	-	-	-	-	5	600 V ac
CQ4 02, CQ4 02 H	2	14 STR	23.0	600 V ac/dc	-	-	-	-	-	-	-	25.0	-	-	-	-	-	5	600 V ac
CQ4 03	3	12 STR	30.0	600 V ac/dc	-	-	-	-	-	-	-	30.0	-	-	-	-	-	5	600 V ac
CQ4 02, CQ4 02 H	2	12 STR	30.0	600 V ac/dc	-	-	-	-	-	-	-	30.0	-	-	-	-	-	5	600 V ac
CQ4 03	3	10 STR	40.0	600 V ac/dc	-	-	-	-	-	-	-	40.0	-	-	-	-	-	5	600 V ac
CQ4 02, CQ4 02 H	2	10 STR	40.0	600 V ac/dc	-	-	-	-	-	-	-	40.0	-	-	-	-	-	5	600 V ac
CQ4 03	3	8 STR	40.0	600 V ac/dc	-	-	-	-	-	-	-	50.0	-	-	-	-	-	5	600 V ac
CQ4 02, CQ4 02 H	2	8 STR	40.0	600 V ac/dc	-	-	-	-	-	-	-	50.0	-	-	-	-	-	5	600 V ac
CQ4 03/2	3	10 STR	37.0	600 V ac/dc	-	-	-	-	-	-	-	40.0	-	-	-	-	-	5	600 V ac
CQ4 03/2	3	12 STR	30.0	600 V ac/dc	-	-	-	-	-	-	-	30.0	-	-	-	-	-	5	600 V ac

CQ4 03/2	3	14 STR	23.0	600 V ac/dc	-	-	-	-	-	-	-	25.0	-	-	-	-	5	600 V ac
-------------	---	-----------	------	----------------	---	---	---	---	---	---	---	------	---	---	---	---	---	----------------

Marking: Company name or trademark  , catalog designation and the Recognized Component Mark  on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2021-07-19

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"