


Part number

CTF 16 R



Female insert, CT series, screw terminal connection, 16 poles + PE, 16 A 230/400 V 4 kV 2, size "77.27", with incorporated terminal block, right side mounting

Product description		Material properties	
Product type	Insert	Main material	Polycarbonate (PC)
Series	CT	Other materials	Contacts: copper alloy
Connection type	Screw terminal connection	Colour	RAL 7032 grey
Gender	Female		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	16 poles + 	RoHs conformity	
Size	Size 77.27	China RoHs - EFUP	50
Specification	Right side mounting With incorporated terminal block	REACH SVHC substances	Yes Lead
Technical data		SCIP number	1a9c93ff-0445-4a16-81e3-1609ac5274d6
Current	16 A	Approvals / Standards	
Voltage	230 - 400 V	Reference standard	EN 61984:2009-06
Rated impulse withstand voltage	4 kV	Certifications	CSA, CQC, DNV, BV, EAC
Pollution degree	2	UL	ECBT2
Rated voltage according to UL/CSA	600 V	General ordering information	
Wire cross-section	0,75 mm ² - 2,50 mm ²	EAN13 code	8015747040785
AWG size	18 - 14	eCl@ss 8.1	27440205
Contact type	Turned silver plated	ETIM 7.0	EC000438
IP degree of protection	IP20 without enclosure, IP66/IP69 with enclosure	Packaging Information	
Further technical details		Packaging weight	0,77 kg
Characteristics according to EN 61984	10A 230/400V 4kV 3; 10A 400V 4kV 2	Packaging description	Carton box
Mating cycles	≥ 500	Packaging quantity	4 Pcs
Insulation resistance	≥ 10 GΩ	Packaging EAN code	8015747040792
Contact resistance	≤ 4 mΩ	Sub-packaging length	145,00 mm
Weight	182,50 g	Sub-packaging height	89,00 mm
Operating temperature range (min, max)	-40 °C ... +125 °C	Sub-packaging width	90,00 mm
Conductors stripping length	12 mm	Sub-packaging weight	0,19 kg
UL 94 flammability rating	V-0	Sub-packaging volume	1,16 dm ³
Torque for main contact	M2,6: 0,4 Nm; 3,5 lb.in (0,5 x 3 mm)	Sub-packaging description	Plastic packaging
Tightening torque for PE connection	M4: 1,2 Nm, 10,6 lb.in (Ph2 or 1,0x5,5mm)	Sub-packaging quantity	1 Pcs
Tightening torque for fixing screws	M3: 0.5 Nm; 4.4 lb.in (Ph1 or 0.8x4 mm)	Sub-packaging EAN barcode	8015747040808

Part number

CTF 16 R



Catalogue drawings

