

Part number

CXFA 10



Female crimp contact, CX series, 40 A, turned silver plated, wire cross section 10 mm², AWG 8, cable diameter up to 7,5 mm

Product description

Product type	Crimp contact
Series	CX
Gender	Female

Technical data

Current	40 A
Wire cross-section	10,00 mm ²
AWG size	8
Contact type	Turned silver plated

Further technical details

Weight	2,70 g
Conductors stripping length	15 mm

Material properties

Main material	Copper alloy
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	C0979fba-9907-458f-a94a-db781440f273

Approvals / Standards

Certifications	CSA, EAC
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747188081
eCl@ss 8.1	27440204
ETIM 7.0	EC000796

Packaging Information


Packaging length	112,00 mm
Packaging height	95,00 mm
Packaging width	117,00 mm
Packaging weight	1,25 kg
Packaging volume	1,24 dm ³
Packaging description	Carton box
Packaging quantity	400 Pcs
Packaging EAN code	8015747179096
Sub-packaging length	50,00 mm
Sub-packaging height	44,00 mm
Sub-packaging width	50,00 mm
Sub-packaging weight	0,16 kg
Sub-packaging volume	0,11 dm ³
Sub-packaging description	Plastic box
Sub-packaging quantity	50 Pcs
Sub-packaging EAN barcode	8015747188210

Part number

CXFA 10



Catalogue drawings



CXF and CXM contacts

conductor cross-sectional area (mm ²)	conductor slot $\varnothing A$ (mm)	conductor stripping length B (mm)
1,5	1,8	9
2,5	2,2	9
4	2,85	9,6
6	3,5	9,6
10	4,3	15